
# SHEPHERDS BAY, MEADOWBANK CIVIL WORKS



#### LOCALITY PLAN

#### DRAWING INDEX

DRG No.	DESCRIPTION	DRG No.	DESCRIPTION
C-0200	COVER SHEET	C-0260	STORMWATER LONGITUDINAL SECTIONS - SHEET 1
C-0201	NOTES SHEET	C-0261	STORMWATER LONGITUDINAL SECTIONS - SHEET 2
C-0202	KEY PLAN	C-0262	STORMWATER LONGITUDINAL SECTIONS - SHEET 3
C-0210	SITEWORKS PLAN - SHEET 1	C-0263	STORMWATER LONGITUDINAL SECTIONS - SHEET 4
C-0211	SITEWORKS PLAN - SHEET 2	C-0264	STORMWATER PIT SCHEDULE
C-0212	SITEWORKS PLAN - SHEET 3	C-0265	CATCHMENT PLAN
C-0213	SITEWORKS PLAN - SHEET 4	C-0270	SIGNAGE AND LINEMARKING PLAN - SHEET 1
C-0214	SITEWORKS PLAN - SHEET 5	C-0271	SIGNAGE AND LINEMARKING PLAN - SHEET 2
C-0215	SITEWORKS PLAN - SHEET 6	C-0272	SIGNAGE AND LINEMARKING PLAN - SHEET 3
C-0230	TYPICAL ROAD SECTIONS	C-0273	SIGNAGE AND LINEMARKING PLAN - SHEET 4
C-0240	CONSTITUTION ROAD LONGITUDINAL SECTIONS	C-0280	DETAILS SHEET 1
C-0245	CONSTITUTION ROAD CROSS SECTIONS - SHEET 1	C-0281	DETAILS SHEET 2
C-0246	CONSTITUTION ROAD CROSS SECTIONS - SHEET 2	C-0282	DETAILS SHEET 3
C-0247	CONSTITUTION ROAD CROSS SECTIONS - SHEET 3	C-0290	TURNING PATH PLAN - SHEET 1
C-0250	INTERSECTION PLAN CONSTITUTION ROAD/BOWDEN STREET	C-0291	TURNING PATH PLAN - SHEET 2



P\BGE\SYD\S10076\100 DRAW\100.2 CIVIL\AUTOCAD\S10076-DRG-C-0200.

A DCSE Dty II

#### GENERAL NOTES

- TECHNICAL SPECIFICATIONS OR SPECIFIC INSTRUCTIONS ON DRAWINGS TAKE PRECEDENCE OVER THESE NOTES.
- DO NOT DEPART FROM THE DESIGN UNLESS AUTHORISED IN WRITING BY THE
- THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL AND OTHER CONSULTANTS: DRAWINGS AND SPECIFICATIONS AND WITH ANY OTHER WRITTEN INSTRUCTIONS AS MAY BE ISSUED DURING THE COURSE OF THE CONTRACT. ANY DISCREPANCY SHALL BE REFERRED TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK. CONSTRUCTION FROM THESE DRAWINGS, AND THEIR ASSOCIATED CONSULTANTS' DRAWINGS IS NOT TO COMMENCE UNTIL APPROVED BY THE RELEVANT AUTHORITIES.
- REFER TO ALL NOTES ON THESE DRAWINGS AND PREVIOUSLY MENTIONED DOCUMENTATION BEFORE BEGINNING CIVIL WORKS.
- ALL MATERIALS AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE ALL MATERIALS AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE RELEVANT AND CURRENT SPECIFIED STANDARDS AND WITH THE BY-LAWS AND ORDINANCES OF THE RELEVANT APPROVAL AUTHORITIES EXCEPT WHERE VARIED BY THE PROJECT SPECIFICATION AND/OR DRAWINGS.
- THE RELEVANT AUTHORITIES OCCUPATIONAL HEALTH AND SAFETY PRACTICES
- ALL DIMENSIONS AND LEVELS SHOWN ON THE DRAWINGS SHALL BE VERIFIED BY THE CONTRACTOR ON SITE CIVIL DRAWINGS SHALL NOT BE SCALED FOR DIMENSIONS. REFER TO ARCHITECTURAL DRAWINGS FOR ALL DIMENSIONS AND THE ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCIES PRIOR TO
- UNLESS NOTED OTHERWISE, ALL DIMENSIONS ARE IN METRES (m) AND ALL LEVELS ARE IN METRES (m) TO AUSTRALIAN HEIGHT DATUM (AHD).
- GRADES TO PAVEMENTS TO BE AS IMPLIED BY RL'S ON CIVIL GRADING PLAN DRAWINGS. GRADE EVENLY BETWEEN NOMINATED RL'S. ON CIVIL GRADING PLAN PONDING GREATER THAN 5mm DEPTH WILL NOT BE ACCEPTED/ UNLESS IN A DESIGNATED SAG POINT.
- 10. IF THERE IS DOUBT REGARDING THE CIVIL DESIGN, CONTACT THE ENGINEER FOR
- 11. ALL ABBREVIATIONS ARE AS FOLLOWS:

EXISTING GROUND LEVEL FINISHED FLOOR LEVEL
REDUCED LEVEL
EASTING COORDINATE NORTHING COORDINATE AUSTRALIAN HEIGHT DATUM U.N.O. UNLESS NOTED OTHERWISE UNPLASTICISED POLYVINYL CHLORIDE REINFORCED CONCRETE PIPE VITRIFIED CLAY PIPE FIRRE REINFORCED COMPOSITE FINISHED SURFACE LEVEL
KERB AND GUTTER
KERB ONLY
NOMINAL FACE OF KERB FLUSH KERB TOP OF KERB BACK OF KERB DISH DRAIN MOUNTABLE KERB MOUNTABLE INTEGRAL KERB INTEGRAL KERB INVERT LEVEL OBVERT LEVEL GRATED DRAIN TOP WATER LEVEL GALV. GALVANISED THICKENED EDGE FLUSHING POINT DOWN PIPE RETAINING WALL
ISOLATION JOINT
DOWELLED EXPANSION JOINT
SAWN JOINT KEYED JOINT TROWELED WEAKENED PLANE JOINT EXPANSION JOINT TOP OF WALL LEVEL

#### BULK EARTHWORKS NOTES

MAP GRID OF AUSTRALIA

- REFER TO GEOTECHNICAL INVESTIGATION REPORT FOR INFORMATION RELATING TO EXISTING GROUND CONDITIONS, GROUND WATER LEVELS, SITE TREATMENT AND
- 6.2. REFER TO 'EXISTING SERVICES AND FEATURES' NOTES BEFORE COMMENCING BULK
- 6.3. TECHNICAL SPECIFICATIONS OR SPECIFIC INSTRUCTIONS CONTAINED IN THE GEOTECHNICAL REPORT TAKE PRECEDENCE OVER THESE NOTES.
- 6.4. ALL TOP SOIL, ORGANIC MATTER AND FILL MATERIAL SHALL BE REMOVED FROM ALL AREAS UNDER PROPOSED WORK LOCATIONS TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER. AREAS TO BE FULLY STRIPPED OF EXISTING FILL AND DARK BROWN BLACK UPPER ORGANIC ALLUVIUM.
- 6.5. CONTRACTOR SHALL PLACE SAFETY BARRIERS AROUND EXCAVATIONS IN ACCORDANCE WITH RELEVANT AUTHORITY SAFETY REGULATIONS
- 6.6. BULK EARTHWORKS DRAWINGS ARE NOT TO BE USED FOR DETAIL EXCAVATION

#### SURVEY NOTES

- THE EXISTING SITE CONDITIONS SHOWN ON THE FOLLOWING DRAWINGS HAVE BEEN DERIVED FROM SURVEY INFORMATION SUPPLIED FROM H RAMSAY & COMPANY PTY LIMITED
- THE FOLLOWING SURVEY INFORMATION HAS BEEN TAKEN DIRECTLY FROM ORIGINAL SURVEY DOCUMENTS.

ORIGIN OF LEVELS SSM 1044 RL 2.55 (AHD)

- THE INFORMATION IS SHOWN TO PROVIDE A BASIS FOR DESIGN. BG&E PTY LTD DOES NOT GUARANTEE THE ACCURACY OR COMPLETENESS OF THE SURVEY BASE OR ITS SUITABILITY AS A BASIS FOR CONSTRUCTION DRAWINGS.
- SHOULD DISCREPANCIES BE ENCOUNTERED DURING CONSTRUCTION BETWEEN THE SURVEY DATA AND ACTUAL FIELD DATA, CONTACT BG&E PTY LTD.
- THE CONTRACTOR SHALL ARRANGE ALL SURVEY SETOUT TO BE CARRIED OUT
- BENCH MARK, SURVEY PEGS, LEVEL PEGS OR SUPPLEMENTARY REFERENCE MARKS SHALL NOT BE ADJUSTED OR MOVED WITHOUT WRITTEN APPROVAL FROM THE SUPERINTENDENT. THE CONTRACTOR SHALL TRANSFER ANY PEGS AFFECTED BY THE PROPOSED WORKS TO SIDE POSITIONS CLEAR OF OPERATIONS AND SHALL NOTE THE EXTENT OF THE MOVEMENT IN DISTANCE AND LEVEL

#### EXISTING SERVICES AND FEATURES NOTES

- THE CONTRACTOR MUST CONFIRM THE EXACT LOCATION AND EXTENT OF EXISTING SERVICES PRIOR TO CONSTRUCTION AND NOTIFY ANY CONFLICT WITH THE DRAWINGS IMMEDIATELY TO THE ENGINEER/SUPERINTENDENT.
- EXISTING SERVICES UNLESS SHOWN ON SURVEY PLAN HAVE BEEN PLOTTED FROM SERVICES SEARCH PLANS AND AS SUCH THEIR ACCURACY CANNOT BE GUARANTEED.
- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO COMPLETE A 'DIAL BEFORE YOU DIG' SEARCH AND TO ESTABLISH THE LOCATION AND LEVEL OF ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF ANY WORK, ANY DISCREPANCIES SHALL BE REPORTED TO THE ENGINEER/SUPERINTENDENT LEARANCES SHALL BE OBTAINED FROM THE RELEVANT SERVICE AUTHORITY. SEARCH RESULTS ARE TO BE KEPT ON SITE AT ALL TIMES.
- THE CONTRACTOR HAS A DUTY OF CARE WHEN EXCAVATING NEAR SERVICES. DO NOT ASSUME DEPTHS OR ALIGNMENTS OF CABLES OR PLANT AS THESE MAY VARY SIGNIFICANTLY. THE CONTRACTOR MUST ACCEPT ALL RESPONSIBILITY TO DAMAGES TO EXISTING SERVICES ANS SERVICE AUTHORITIES MAY SERK COMPENSATION FOR DAMAGES CAUSED TO THEIR PROPERTY AND SUBSEQUENT
- THE CONTRACTOR SHALL ALLOW FOR THE CAPPING OFF, EXCAVATION AND REMOVAL OR RELOCATION (IF REQUIRED) TO RELEVANT AUTHORITIES GUIDELINES OF ALL EXISTING SERVICES IN AREAS AFFECTED BY WORKS WITHIN THE CONTRACT AREA OR AS SHOWN ON THE DRAWINGS UNLESS DIRECTED OTHERWISE BY THE ENGINEER/SUPERINTENDENT.
- INTERRUPTION TO SUPPLY OF EXISTING SERVICES SHALL BE DONE SO AS NOT TO CAUSE ANY INCONVENIENCE TO SURROUNDING ALLOTMENTS, CONTRACTOR TO GAIN APPROVAL FROM THE RELEVANT AUTHORITIES FOR TIME OF INTERRUPTION
- THE CONTRACTOR SHALL CONSTRUCT TEMPORARY SERVICES TO MAINTAIN THE CONTRACTOR SHALL CONSTRUCT TEMPORARY SERVICES TO MAINTAIN SUPPLY TO EXISTING BUILDINGS REMAINING IN OPERATION DURING WORKS TO THE SATISFACTION AND APPROVAL OF ANY RELEVANT AUTHORTIES. ONCE DUVERSION IS COMPLETE AND COMMISSIONED, THE CONTRACTOR SHALL REMOVE ALL SUCH TEMPORARY SERVICES AND MAKE GOOD TO THE SATISFACTION OF THE RELEVANT AUTHORITY/SUPERINTENDENT
- EXISTING SERVICES, BUILDINGS, EXTERNAL STRUCTURES AND TREES SHOWN ON THESE DRAWINGS ARE EXISTING FEATURES PRIOR TO ANY DEMOLITION WORKS.
- ALL BRANCH GAS AND WATER SERVICES LINDER DRIVEWAYS BRICK PAVING AND CONSTRUCTION TRAFFIC MANEUVERING AREAS SHALL BE PROTECTED TO RELEVANT AUTHORITIES GUIDELINES.
- ALL EXISTING SERVICE UTILITIES COVERS AND GRATES ARE TO BE ADJUSTED (TO RELEVANT AUTHORITY GUIDELINES) TO SUIT NEW FINISHED SURFACE LEVELS WHERE APPLICABLE.
- IF EXISTING SERVICE UTILITY COVERS AND GRATES OR SURROUNDING SURFACE LEVELS ARE TO BE LOWERED, THE CONTRACTOR IS TO MAKE CERTAIN THAT MINIMUM COVERS (TO RELEVANT SERVICE AUTHORITY GUIDELINES) TO SERVICES ARE MAINTAINED. IF MINIMUM COVERS AREN'T MAINTAINED THE CONTRACTOR IS TO LOWER OR PROTECT SERVICES TO THE SATISFACTION OF THE RELEVANT SERVICE AUTHORITY/SUPERINTENDENT.

#### SUBSOIL DRAINAGE NOTES

- PROVIDE SUBSOIL DRAINS TO INTERCEPT GROUNDWATER SEEPAGE AND PREVENT WATER BUILD-UP BEHIND WALLS AND UNDER FLOORS AND PAVEMENTS. CONNECT SUBSOIL TO SURFACE DRAINS OR TO THE STORMWATER DRAINAGE SYSTEM AS APPLICABLE.
- ALL SUBSOIL PIPES SHALL BE 100mm SLOTTED CORRUGATED uPVC IN A FILTER SOCK U.N.O.
- FILTER SOCKS ARE TO BE POLYESTER PERMEABLE SOCKS CAPABLE OF RETAINING PARTICLES GREATER THAN 0.25mm IN SIZE. SECURELY FIT OR JOIN THE SOCK AT EACH JOINT.
- WHERE SUBSOIL DRAINS PASS UNDER EXTERNAL SLABS AND VEHICULAR PAVEMENTS, UNSLOTTED uPVC SEWER GRADE PIPE IS TO BE USED.
- SUBSOIL DRAINAGE TRENCHES ARE TO BE WRAPPED WITH PERMEABLE TEXTILE FABRIC 'BIDIM A12' OR EQUIVALENT.
- TO REDUCE GROUND WATER TRACKING WITHIN STORMWATER TRENCHES INSTALL A 3m LENGTH OF SUBSOIL PIPE IN PIPE TRENCHES DRAINING IN DIRECTION OF FALL OF PIPE AND CONNECT TO DOWNSTREAM STORMWATER DRAINAGE PIT.
- Subsoil Minimum Clearance Depths, Measured to the Crown of the Pipe, Where the Pipe Passes Below the Following Elements:

  100mm below Formation Level of the Payement, Kerb or Channel.
  At the Average Gradient of the Bottom of Footings.
- AT JUNCTIONS OF SUBSOIL PIPES PROVIDE TEES, COUPLINGS OR ADAPTORS IN
- SUBSOIL DRAINAGE TRENCHES SHALL BE A MINIMUM 300mm WIDE.
- 10 GRADE THE TRENCH FLOOR EVENLY TO THE GRADIENT OF THE PIPELINE IF THE GRADE THE TREMP FLOOR EVENT TO THE WARDLEN OF THE PIPELINE. IF THE TRENCH FLOOR IS ROCK, CORRECT ANY IRREGULARITIES WITH COMPACTED BEDDING MATERIAL, BED PIPING ON A CONTINUOUS UNDERLAY OF BEDDING MATERIAL, BED PIPING ON A CONTINUOUS UNDERLAY OF BEDDING MATERIAL, AT LEAST 75mm THICK AFTER COMPACTION. LAY THE PIPE WITH ONE LINE OF PERFORATIONS AT THE BOTTOM.
- EQUAL TO 200mm LOOSE THICKNESS, AND COMPACT WITHOUT DAMAGING OR DISPLACING PIPING.

#### SUBGRADE COMPACTION NOTES

- THE EXPOSED SUBGRADE (LE. THE LOWER COURSE OF PAVEMENT BELOW THE THE EXPOSED SUBGRADE (IE. THE LOWER COURSE OF PAYEMENT BELOW THE SUB-BASE) AFTER STRIPPING AND/OR EXCAVATION SHALL BE PROOF ROLLED USING NOT FEWER THAN 5 PASSES WITH A 10 TONNE DEAD WEIGHT STEEL SMOOTH-DRUM ROLLER UNDER THE SUPERVISION OF AN EXPERIENCED GEOTECHNICAL ENGINEER. ANY AREAS EXHIBITING EXCESSIVE DEFLECTION/MOVEMENT UNDER ROLLER SHALL BE REMOVED TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER TO A MINIMUM DEPTH OF 500mm AND THEN AND AND THEN THE GEOTECHNICAL ENGINEER TO A MINIMUM DEPTH OF 500mm AND THEN AND AND THEN THE SECOND OF THE SATISFACTION OF THE GEOTECHNICAL ENGINEER TO BE MINIMUM DEPTH OF 500mm AND THEN SATISFACTION OF THE GEOTECHNICAL ENGINEER TO A MINIMUM DEPTH OF 500mm AND THEN SATISFACTION OF THE SECOND OF THE SECOND OF THE SATISFACTION OF THE SECOND OF TH BACKFILLED WITH APPROVED ENGINEERED FILL TO MEET THE DESIGN SUBGRADE
- 2. ENGINEERED FILL TO TO BE PLACED IN LAYERS NOT EXCEEDING 250mm LOOSE THICKNESS AND COMPACTED TO 98% OF STANDARD MAXIMUM DRY DENSITY (SMDD) AND TO WITHIN 2% OF STANDARD OPTIMUM MOISTURE CONTENT (SOMC) IN ACCORDANCE WITH AS 1289 5.11. APPROVED BACKFILL MATERIAL MAY BE CRUSHED ROCK OR SANDY LOAM WITH A PLASTICITY INDEX LESS THAN 15%.
- 3. TESTING OF THE SUBGRADE SHALL BE CARRIED OUT BY AN APPROVED N.A.T.A. REGISTERED LABORATORY
- 4. ALL FILL MATERIAL SHALL BE FROM A SOURCE APPROVED BY THE ALL FILL MATERIAL STALL DE INVA A SOURCE APPROVED 6

  FREE FROM ORGANIC AND PERISHABLE MATTER

  MAXIMUM PARTICLE SIZE = 75mm

  MAXIMUM PLASTICITY INDEX = 15%

#### SUB-BASE COURSE COMPACTION NOTES

- PAVEMENT "SUB-BASE" (I.E THE INTERMEDIATE OR LOWER COURSE OF THE PAVEMENT BELOW THE BASE) SHALL BE CONSTRUCTED FROM MATERIAL AS SPECIFIED ON DRAWINGS AND COMPACTED TO 98% OF THE STANDARD MAXIMUM DRY DENSITY (SMDD) AND WITHIN 2% OF STANDARD OPTIMUM MOISTURE CONTENT
- ALL SUB-BASE MATERIAL SHALL BE HARD, DURABLE AND THE MATERIALS SHALL BE FREE OF CLAY LUMPS, ORGANIC MATTER AND OBJECTIONABLE QUANTITIES OF DELETERIOUS SUBSTANCES.
- 3. ALL MATERIAL REQUIREMENTS APPLY BOTH PRIOR TO AND AFTER PLACEMENT OF

#### BASE COURSE COMPACTION NOTES

- 1. PAVEMENT "BASE" (I.E THE HIGHEST COURSE OF THE PAVEMENT BELOW THE SURFACING) SHALL BE CONSTRUCTED FROM MATERIAL AS SPECIFED ON DRAWINGS AND COMPACTED TO 98% OF THE STANDARD MAXIMUM DRY DENSITY (SMDD) AND WITHIN 2% OF STANDARD OPTIMUM MOISTURE CONTENT (SOMC) IN ACCORDANCE WITH AS 1289 5.1.1 (EXCEPT CONCRETE PAVEMENT, WHERE THE CONCRETE IS THE
- 2. ALL BASE MATERIAL SHALL BE HARD, DURABLE AND THE MATERIALS SHALL BE FREE OF CLAY LUMPS, ORGANIC MATTER AND OBJECTIONABLE QUANTITIES OF DELETERIOUS SUBSTANCES.
- 3. ALL MATERIAL REQUIREMENTS APPLY BOTH PRIOR TO AND AFTER PLACEMENT OF

#### GENERAL PAVEMENT NOTES

- TECHNICAL SPECIFICATIONS CONTAINED WITHIN THE GEOTECHNICAL REPORT TAKE PRECEDENCE OVER THESE NOTES.
- PRIOR TO DELIVERY OF ANY MATERIAL TO THE SITE, THE SOURCE OF ALI MATERIALS AND ANY RELEVANT CERTIFICATES STATING THAT THE MATERIAL SATISFIES THE SPECIFIED REQUIREMENTS SHALL BE PROVIDED TO THE SUPERINTENDENT FOR APPROVAL
- TESTING OF PAVEMENT MATERIALS WILL NORMALLY BE PERFORMED ON SAMPLES TAKEN AT THE SOURCE SITE PRIOR TO DELIVERY TO THE SITE AND IN THEIR FINAL CONDITIONS AFTER PLACEMENT AND COMPACTION. HOWEVER, THE PROPERTIES SPECIFIED AND FINAL ACCEPTANCE ARE APPLICABLE TO THE MATERIALS IN THEIR FINAL CONDITION IN THE PAVEMENT.
- 4. FINAL ACCEPTANCE WILL BE CONDITIONAL ON NO SIGNIFICANT CHANGE IN PROPERTIES DUE TO SEGREGATION OR CONTAMINATION DURING SUBSEQUENT PAVEMENT WORKS

#### STORMWATER DRAINAGE NOTES

- THE STORMWATER DESIGN SHOWN ON THESE DRAWINGS HAS BEEN CARRIED OUT IN ACCORDANCE WITH CITY OF RYDE COUNCIL'S REQUIREMENTS, AUSTRALIAN RAINFALL AND RUNOFF (AR&R) GUIDELINES AND RELEVANT AUTHORITIES
- FINISHED SURFACE LEVELS SHOWN ON CIVIL GRADING PLAN DRAWINGS TAKE PRECEDENCE OVER DRAINAGE LONGSECTION SURFACE LEVELS.
- ALL STORMWATER WORK IS TO COMPLY WITH AS3500 PART 3
- PROTECTION OF PIPES EXPOSED TO LOADS EXCEEDING THE W7 WHEEL LOAD OF 70kN SHALL BE THE CONTRACTOR'S RESPONSIBILITY.
- NO CONSTRUCTION LOADS SHALL BE APPLIED TO upvc PIPES.
- EXISTING STORMWATER PIPE LOCATIONS AND INVERT LEVELS TO BE CONFIRMED PRIOR TO COMMENCEMENT OF CONSTRUCTION
- FOR ALL STORMWATER DRAINAGE PITS REFER TO TYPICAL PIT CHAMBER DETAILS ON THESE DRAWINGS. IF PIT LID SIZE IS SMALLER THAN THE PIT CHAMBER SIZE THEN THE PIT LID IS TO BE CONSTRUCTED ON THE CORNER OF THE PIT CHAMBER WITH THE STEP IRONS DIRECTLY BELOW. ALTERNATIVELY THE PIT LID TO BE LISED. IS TO BE THE SAME SIZE AS THE PIT CHAMBER.
- GALVANIZED STEP IRONS SHALL BE PROVIDED AT 300 CTRS FOR PITS HAVING A
- PIPES 300 DIA. AND LARGER TO BE REINFORCED CONCRETE PIPES (RCP) CLASS '4' APPROVED SPIGOT AND SOCKET WITH RUBBER RING JOINTS U.N.O.
- 10. PIPES UP TO 300 DIA, SHALL BE SEWER GRADE uPVC WITH SOLVENT WELDED
- EQUIVALENT STRENGTH VCP OR FRC PIPES MAY BE USED IF RELEVANT

APPROVAL AUTHORITY AND SUPERINTENDENT PERMITS.

- BEDDING TYPE SHALL BE TYPE HS2 FOR RCP CONFORMING TO AS4058. WHERE RECESSARY THE OVERLAY ZONE SHALL BE REDUCED TO ACCOMMODATE PAVEMENT REQUIREMENTS.
- 13. PIPES SHALL BE LAID ON A 75mm THICK SAND BED. IN ALL CASES BACKFILL TRENCH WITH SAND TO 200mm ABOVE THE PIPE. WHERE PIPE IS UNDER PAVEMENTS BACKFILL REMAINDER OF TRENCH TO UNDERSIDE OF PAVEMENT WITH SAND OR APPROVED GRANULAR MATERIAL COMPACTED IN ISOMM LAYERS TO 98% STANDARD MAXIMUM DRY DENSITY IN ACCORDANCE WITH AS 1289 5.2.1 (OR A DENSITY INDEX OF NOT LESS THAN 75).
- 14. WHERE TRENCHES ARE IN ROCK THE PIPE SHALL BE BEDDED ON A MINIMUM OF 50mm CONCRETE BED (OR 75mm BED OF 12mm BLUE METAL) UNDER THE BARREL
- 15. ENLARGERS, CONNECTORS AND JUNCTIONS TO BE PREFABRICATED FITTINGS WHERE PIPES ARE LESS THAN 300 DIA.
- CARE IS TO BE TAKEN WITH LEVELS OF STORMWATER LINES. GRADES SHOWN ARE NOT TO BE REDUCED WITHOUT PRIOR WRITTEN APPROVAL FROM THE
- 17. GRATES AND COVERS SHALL CONFORM TO AS3996 AND AS1428.1 AT ALL TIMES DURING CONSTRUCTION OF THE STORMWATER PITS.
- ALL EXISTING STORMWATER DRAINAGE LINES AND PITS THAT ARE TO REMAIN ARE TO BE INSPECTED AND CLEANED. DURING THIS PROCESS ANY PART OF THE STORMMATER DRAINAGE SYSTEM THAT WARRANTS REPAIR SHALL BE REPORTED TO THE SUPERINTENDENT AND ENGINEER FOR FURTHER DIRECTIONS.

#### KERBING NOTES

INCLUDES ALL KERBS, GUTTERS, DISH DRAINS, CROSSINGS AND EDGES.

- ALL KERBS, GUTTERS, DISH DRAINS AND CROSSINGS TO BE CONSTRUCTED ON MINIMUM 75mm GRANULAR BASE COURSE MATERIAL COMPACTED TO A MINIMUM 98% MODIFIED MAXIMUM DRY DENSITY IN ACCORDANCE WITH AS 1289 5.2.1.
- EXPANSION JOINTS (EJ) TO BE FORMED FROM 10MM COMPRESSIBLE CORK FILLER BOARD FOR THE FULL DEPTH OF THE SECTION AND CUT TO PROFILE EXPANSION JOINTS TO BE LOCATED AT DRAINAGE PITS, ON TANGENT POINTS OF CURVES AND ELSEWHERE AT 12M CENTRES EXCEPT FOR INTEGRAL KERBS WHERE THE EXPANSION JOINTS ARE TO MATCH THE JOINT LOCATIONS IN SLABS.
- WEAKENED PLANE JOINTS (WPJ) ARE TO BE LOCATED AT A MAX 1.5 x WIDTH OF THE PAVEMENT. WEAKENED PLANE JOINTS (WP.) ARE TO BE A MINIMUM 3mm WIDE WITH A JOINT DEPTH TO BE A MINIMUM OF 1/4 THE TOTAL DEPTH OF THE
- 4. ALL KERBING OR DISH DRAINS TO BE STEEL FLOAT FINISHED.
- WHEN CONSTRUCTING NEW KERB TO EXISTING AND IN THE REPLACEMENT OF KERBS, EXISTING ROAD PAVEMENT IS TO BE SAWCUT 900mm FROM LIP OF GUTTER. UPON COMPLETION OF NEW KERBS, NEW BASE COURSE AND SURFACE IS TO BE LAID 900mm WIDE TO MATCH EXISTING MATERIALS AND THICKNESS.
- EXISTING ALLOTMENT DRAINAGE PIPES ARE TO BE BUILT INTO THE NEW KERB WITH A 125 x 75 GALVANISED RHS.
- EXISTING KERBS ARE TO BE COMPLETELY REMOVED WHERE NEW KERBS ARE

FOR INFORMATIO / DATE DESCRIPTIO REVISIONS

#### HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office E2 2 Windows Sale





SHEPHERDS BAY MFADOWBANK


PRELIMINARY ONLY TR NK


NOTES SHEET


S10076 C-0201





















SECTION 1 SCALE 1:50 C-0213 C-0212



SECTION 2 SCALE 1:50 C-0210



SECTION 3 SCALE 1:50 C-0212



#### HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—
5.2 & Whatell 3: Sydney 265W 2600
P.7452 257F0 258B
B. Tallethympour

**Æ** 

PROJECT

SHEPHERDS BAY
MEADOWBANK


PRELIMINARY ONLY
NOT TO BE USED FOR CONSTRUCTION

TYPICAL ROAD SECTIONS

S14053 | C-0230 | REV.

P\BGE\SYD\S10076\100 DRAW\100.2 CIVIL\AUTOCAD\S10076-DRG-C-0230.DWG

O DCSE Dty I



 $\underset{\text{SCALE 1:500H,}}{\mathsf{PROFILE}} \; \underset{\text{1:100V}}{\mathsf{-}} \; \; \mathsf{CONSTITUTION} \; \; \mathsf{ROAD} \; \; \mathsf{(MC10)}$ 

Α	23.12.14	ISSUED FOR INFORMATION	
REV	DATE	DESCRIPTION	RVI
		REVISIONS	

#### HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—
La 2 Window II: Sydney 2050/ 2
P7-65 a 59792-5900
B/info@compone



PROJECT

SHEPHERDS BAY MEADOWBANK

PRELIMINARY ONLY


NOT TO BE USED FOR CONSTRUCTION


TOESGORED GRECKED TAPPROVED

CONSTITUTION ROAD LONGITUDINAL SECTIONS


PROJECT No. S14053 DRAWING No. C-0240


P:\BGE\SYD\S10076\100 DRAW\100.2 CIVIL\AUTOCAD\S10076-DRG-C-0240.DWG





CHAINAGE 75





CHAINAGE 45

DATUM 10.000 PROPOSED 2.552 2.552 2.402 2.442 12.367 12.327 12.477 12.477 12.638 12.389 12.376 12.306 EXISTING -6.844 -6.819 -6.694 -3.350 -3.225 -3.200 -2.750 OFFSET 5.250 5.700 5.725 5.850 HOLDMARK 2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

A 23.12.14 ISSUED FOR INFORMATION
EEV DATE DESCRIPTION

REVISIONS

Sydney Office—

1.350

SHEPHERDS BAY MEADOWBANK

NOTE
\* - RETAINING WALL BY OTHERS

PRELIMINARY ONLY


CONSTITUTION ROAD CROSS SECTIONS


SHEET 1

		- 3%		2.5%	* PROD. BDY
DATUM 12.000					
PROPOSED	14.698	14.602	14.541 14.651 14.651	14.713	14.788
EXISTING	14.879	14.759	13.833 13.823 13.772	13.248	13.152 13.246
OFFSET	00000	3.200	5.250 5.700 5.725 5.850	8.350	12.236


CHAINAGE 16.19

S14053 C-0245 Α







CHAINAGE 210



CHAINAGE 195



CHAINAGE 180



CHAINAGE 165

A	23.12.14	ISSUED FOR INFORMATION	
REV	DATE	DESCRIPTION	F

#### HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—




SHEPHERDS BAY MEADOWBANK

PRELIMINARY ONLY

CROSS SECTIONS

SHEET 3 S14053

A C-0247



A 23.12.14 ISSUED FOR INFORMATION
REV DATE DESCRIPTION REVISIONS

#### HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—


#### SHEPHERDS BAY MEADOWBANK

PRELIMINARY ONLY

STORMWATER LONGITUDINAL SECTIONS

SHEET 1 S10076

C-0260



A	23.12.14	ISSUED FOR INFORMATION	
REV	DATE	DESCRIPTION	RVD
		REVISIONS	
Sı	dney O	#i T	
12		Al Systemy MSW 2000	¥
	infoffique		TH:
de	Mg.4000		ن
PROJECT			
		SHEPHERDS BAY	

MEADOWBANK


AHD MGA 1:100H, 1:20V AT A1 S

STORMWATER LONGITUDINAL

C-0261

PRELIMINARY ONLY

SECTIONS SHEET 2 DECT No. S10076



φ375 	Ø375 RCP CLASS 2	Ø375 RCP CLASS 2	
RCP CLASS 2 8.49%	RLP CLASS 2 7.54%	RLP LLASS 2 3.78%	
18.54m 1.19m	36.98m 1.1m	30.65m 1.1m	
70L/s	213L/s	295L/s	
3.91m/s	5.12m/s	4.29m/s	
1.398	1.651	1.720	4.050
8.052 8.050	7.674	4.778 3.621 3.020	2.878
7.776	7.523	4.554	0.991
9.174	6.274	5.041	
9.220	6.187	4,937	
18.541	55.520	86.168	
	LINE QC		

A 23.12.14 ISSUED FOR INFORMATION
REV DATE DESCRIPTION REVISIONS

#### HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—


#### SHEPHERDS BAY MEADOWBANK

PRELIMINARY ONLY

STORMWATER LONGITUDINAL SECTIONS

SHEET 3

S10076 C-0262



Α	23.12.14	ISSUED FOR INFORMATION	
REV	DATE	DESCRIPTION	RVE

#### HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—

SHEPHERDS BAY MEADOWBANK


PRELIMINARY ONLY

STORMWATER LONGITUDINAL SECTIONS SHEET 4

S10076

C-0263





A 231214 ISSUED FOR INFORMATION REV DATE DESCRIPTION RV

#### HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—
52 & Whatelfile Sylvey 165W 200
P7452 2570 200
B/Infofficences



SHEPHERDS BAY
MEADOWBANK

PRELIMINARY ONLY
NOT TO BE USED FOR CONSTRUCTION

CATCHMENT PLAN

S10076 C-0265


BG&E Pty Limite

PIT / NODE				Varsian 0			
DETAILS	May HCI	May Dond	May Curfoss	Version 8	Min	Overflow	Constraint
Name	Max HGL	Max Pond	Max Surface	Max Pond	Min	Overflow	Constraint
		HGL	Flow Arriving	Volume	Freeboard	(cu.m/s)	
			(cu.m/s)	(cu.m)	(m)		
NA.1	7.7900	9.0300	11.4550	0.6000	0.4100	0.0000	Inlet Capacit
NA.2	6.8600		0.0090		2.2000	0.0000	
NA.3	6.2700	9.0400	0.0920	5.3000	2.6200	0.0000	Inlet Capacit
NA.4	4.7800		0.0000		1.8700	0.0000	
NA.5	4.2800	5.0700	0.2400	1.7000	0.6900		Inlet Capacit
NA.6	3.9100	5.1800	0.1710	2.1000	1.1300	0.0000	Inlet Capacit
NA.7	3.6800		0.0000		1.8200	0.0000	None
NA.8	3.2500		0.0000		1.9000	0.0000	None
NA.9	2.8500		0.0000		2.3000	0.0000	None
NA.10	2.4200		0.0000		1.1800	0.0000	None
NA.11	2.0100		0.0000		1.9000	0.0000	None
NA.12	1.3700		0.0000		1.6200		None
NA.13	0.4700		0.0000				
OA.1	13.8700		0.3680		0.9700		Inlet Capacit
OA.2	12.8100		0.2560		1.0000	0.0960	Inlet Capacit
OA.3	8.9200		0.1230		1.0300	0.0400	Inlet Capacit
OB.1	9.3100		0.0200		1.3300	0.0000	None
OB.2	9.1400		0.0500		1.3500	0.0100	Inlet Capacit
OB.3	7.7900		0.0330		1.3300	0.0000	None
OC.1	7.9100		0.0130		1.3500	0.0000	
QA.1	6.3300	7.9300	0.0080	0.1000	1.5800	0.0000	Inlet Capacit
QA.2	5.3400	6.9000	0.0100	0.1000	1.5500	0.0000	Inlet Capacit
QA.3	3.9400		0.0170		1.4000	0.0040	Inlet Capacit
QB.1	5.9500	7.5000	0.0180	0.2000	1.5200	0.0000	Inlet Capacit
QB.2	4.8800	6.4800	0.3080	0.9000	1.4900	0.2130	Inlet Capacit
QB.3	4.7000	5.2700	0.2350	0.9000	0.4800		Inlet Capacit
QE.1	5.8000		0.1630		0.5900	0.0830	Inlet Capacit
QC.3	5.7200		0.0260		0.5500	0.0000	None
RA.1	4.8000	5.1800	0.6780	21.5000	0.1000		Inlet Capacit
RB.1	2.7800	4.0200	0.1030	0.4000	1.1600		Inlet Capacit
RC.1	3.8000		0.0740	21.000	1.1800	0.0000	
QF.1	8.4400		0.0440		1.5000	0.0000	
QD.1	8.4100	9.8500	0.2370	0.9000	1.3500	0.1420	Inlet Capacit
QC.2	8.1400	7.0300	0.0190	3.7500	1.0400		Inlet Capacit

Name	Max	Paved	Grassed	Paved	Grassed	Supp.	Due to Storm
	Flow Q	Max Q	Max Q	Tc	Тс	Tc	
	(cu.m/s)	(cu.m/s)	(cu.m/s)	(min)	(min)	(min)	
C NA.2	0.0090	0.0080	0.0010	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C NA.3	0.0580	0.0540	0.0040	5.2400	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C NA.5	0.0250	0.0230	0.0020	5.2900	10.0000	0.0000	9
C NA.6	0.0360	0.0340	0.0030	5.2300	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OA.1	0.3680	0.3430	0.0260	5.0000	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OA.2	0.0760	0.0710	0.0050	5.0900	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OA.3	0.0290	0.0270	0.0020	5.2100	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OB.1	0.0200	0.0190	0.0010	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OB.2	0.0500	0.0470	0.0030	5.0000	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OB.3	0.0240	0.0220	0.0020	5.2100	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OC.1	0.0130	0.0120	0.0010	5.2100	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QA.1	0.0080	0.0080	0.0010	5.0000	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QA.2	0.0100	0.0090	0.0010	5.1000	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QA.3	0.0170	0.0160	0.0010	5.1900	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QB.1	0.0180	0.0170	0.0010	5.0000	10.0000	0.0000	
C QB.2	0.3080	0.2860	0.0220	5.1000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QB.3	0.0220	0.0200	0.0020	5.3300	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C QE.1	0.0210	0.0190	0.0010	5.2000	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QC.3	0.0220	0.0210	0.0020	5.2000	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C RA.1	0.6780	0.5420	0.1360	5.0000	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C RB.1	0.1030	0.0820	0.0210	5.3500	10.0000	0.000	
C RC.1	0.0740	0.0590	0.0150	5.0000	10.0000		AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C QF.1	0.0440	0.0410	0.0030	5.0000	10.0000		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QD.1	0.2370	0.2160	0.0210	10.0000	10.0000		AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C QC.2	0.0090	0.0090	0.0010	5.0900	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C PA.1	0.4480	0.3480	0.1000	10.0000	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C PB.1	0.0290	0.0080	0.0210	5.0000	5.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1


PIPE DETA	ILS				
Name	Max Q	Max V	Max U/S	Max D/S	Due to Storm
	(cu.m/s)	(m/s)	HGL (m)	HGL (m)	
P NA.1	13.9080	4.4700	6.9690	6.8600	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.2	13.9140	4.2800	6.5950	6.2740	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.3	14.2580	7.6900	5.4530	4.7760	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.4	14.3430	7.1900	4.3890	4.2830	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.5	14.8650	3.2900	3.9530	3.9060	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.6	15.1660	3.3500	3.7340	3.6790	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.7	15.1780	3.3600	3.5730	3.2530	3
P NA.8	15.1740	3.3500	3.1800	2.8460	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.9	15.5160	3.4300	2.7930	2.4200	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.10	15.5800	3.5500	2.0590	2.0100	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.11	15.6020	4.0600	1.5040	1.3740	y g
P NA.12	15.5920	5.0400	0.6070	0.4670	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P OA.1	0.2050	3.9500	13.5450	12.8120	AR&R 100 year, 15 minutes storm, average 154 mm/h, Zone 1
P OA.2	0.3320	6.1100	12.3430	8.9180	3
P OA.3	0.4030	4.3000	8.7820	7.6180	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P OB.1	0.0200	1.4300	9.2630		AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P OB.2	0.0610	2.9400	9.0360	7.7950	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P OB.3	0.1040	2.2800	7.7350	7.5400	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1


Name	Max Q	Max V	Max U/S	Max D/S	Due to Storm
rearrio	(cu.m/s)	(m/s)	HGL (m)	HGL (m)	But to storm
P OC.1	0.0130	1.2300	7.8700	7.7950	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QA.1	0.0080	1.8100	6.2960	5.3360	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QA.2	0.0180	2.1800	5.2810	3.9370	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QA.3	0.0310	0.3900	3.9350	3.9060	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P QB.1	0.0180	2.3500	5.8910	4.8850	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QB.2	0.1130	3.4500	4.7160	4.6960	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QB.3	0.2080	1.8800	4.4080	4.2830	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P QE.1	0.0780	0.7000	5.7480	5.7230	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P QC.3	0.3320	4.4000	4.7970	3.9060	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P RA.1	0.6570	3.0900	4.2850	3.5640	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P RB.1	0.1020	2.0100	2.6530	2.6090	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P RC.1	0.1600	7.3200	3.5610	2.0100	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P QF.1	0.0440	0.6900	8.4070	8.4050	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QD.1	0.1390	3.9400	8.2140	8.1360	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QC.2	0.2330	5.2500	7.6810	5.7230	AR&R 100 year, 15 minutes storm, average 154 mm/h, Zone 1
P PA.1	0.1300	1.6300	5.4890		, ,
P PB.1	0.3390	2.1300	5.1080	4.2830	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1




\$10076


C-0270










PLAN - KERB RAMP











BLEND TO EXISTING PAVEMENT DETAIL
SCALE 120












EDGE STRIP (ES)

KERB ONLY (KO)




SECTION THROUGH MOUNTABLE ISLAND SCALE 1:20


A REV	23.12.14 DATE	ISSUED FOR INFORMATION DESCRIPTION	-
		REVISIONS	
CLIENT		A DIV	
H(	OLDM	AKK	
		AKK  AVENUE, MACQUARIE PARK NSW 2113	

ROJECT	
KUJECI	
	SHEPHERDS BAY
	MEADOWBANK


DRAWN	DESIGNED	CHECKED	APPROVED		
TB	NK				
DATUM	GRID	SCALE	•		
AHD	MGA	1:10 1:	20	AT	A1 sız

\$10076 A C-0280





ROAD SIDE BIO-RETENTION



SECTION B
SCALE 1:25 -

A 231214 ISSUED FOR INFORMATION
REV DATE DESCRIPTION
REVISIONS

CLIENT

HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

PROJECT

SHEPHERDS BAY
MEADOWBANK


STATUS


PRELIMINARY ONLY
NOT TO BE USED FOR CONSTRUCTION
DRAWN DESCRED OVERSED APPROVED
TB NK
DATEN OND SCALE
AHD MGA 1:10 1:20 AT


THEE


DETAILS SHEET 2


P\BGE\SYD\S10076\100 DRAW\100.2 CIVIL\AUTOCAD\S10076-DRG-C-0281.DW














A 23.12.14 ESUED FOR INFORMATION REV DATE DESCRIPTION REVO.

HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

8

SHEPHERDS BAY MEADOWBANK

PRELIMINARY ONLY
NOT TO BE USED FOR CONSTRUCTION

DRAWN BESCRED NK OPECNED APPROVED

TB NK SCALE


AHD MGA 1:10 1:20 AT A1


DETAILS SHEET 3

PROJECT No. S10076 DRAWING NO. C-0282

P\BGE\SYD\S10076\100 DRAW\100.2 CIVIL\AUTOCAD\S10076-DRG-C-0282.DWG

A DCRE Dtv Limito







# MEADOWBANK, SHEPHERDS BAY Stages 8-9

detailed landscape + public domain plan

Development Assessment Submission Project Ref: HOL07

> 16 January 2015 Issue [C]

DOCUMENT REGISTER			
Document Name	For	Date	Issue
Meadowbank Stages 8-9 Detailed Landscape + Public Domain Plan	Development Assessment Submission	17.12.2014	А
Meadowbank Stages 8-9 Detailed Landscape + Public Domain Plan	Development Assessment Submission	18.12.2014	В
Meadowbank Stages 8-9 Detailed Landscape + Public Domain Plan	Development Assessment Submission	16.01.2015	С



Introduction	4
Development Control Conditions	5
Pedestrian + Cycleway Plan (Development Wide)	6
Street Tree Strategy (Development Wide)	7
DESIGN: THE MASTERPLAN	
Landscape Design Intent Statement	8
Stages 6-7+ 8-9 Combined Masterplan	9
Stages 8-9 Masterplan	10
The Escarpment / Central Spine	11
Public Open Space / Private Open Space - Building 8	13
West Podium Link Buildings 9A - 9B	15
Building 9B Foyer + Cafe	16
.East Site Link Building 8 / Stage 3 + Adjacent Property	17
Nancarrow Road Frontage	18
Bowden Street Frontage	19
STRATEGY: SITE + ELEMENTS	
Tree + Softscape Strategy	19
Indicative Planting Stragety + Schedule	20
Streetscape Strategy	21
Tree Retention / Removal Strategy	22
Landscape Materiality	23
Materails Strategy Diagram	24
Lighting Strategy Diagram	25
Furniture Strategy Diagram	29
Rooftop Garden Strategy	27

#### APPENDICIES

A Performance Specification

B Detailed Landscape Grading Plan

## INTRODUCTION

"The project represents an opportunity to bring about positive change in current residential design trends by celebrating and bringing to life both the natural landscape and rich cultural history of the site in the landscape of the new development"

This document outlines the proposed Landscape Design Concept (DA) that fulfills the conditions of and guidelines set in the Major Project. Concept Plan Application for the Shepherds Bay residential development.

The project represents an opportunity to bring about positive change in current residential design trends by celebrating and bringing to life both the natural landscape and rich cultural history of the site in the landscape of the new development. It will also ensure that the Shepherds Bay site Landscape Design meets both the Proponents vision for the site and Council's planning objectives, long term objectives and area specific Public Domain Manual,

The landscape design provides solutions that reflect the image and character of the Shepherds Bay Site as a fully integrated residential / parkland environment reflecting both the history and culture of the site.

Water usage, recycling and movement are a key part of this history and will be reflected throughout the landscape design. The landscape design will draw upon a rich and varied site history:- the aim to enhance and create a culturally significant landscape setting that transcends past and present. In this way the landscape will serve to educate visitors and residents whilst enhancing the sense of place and creating a unique identity for Shepherds Bay

The enjoyable and safe interaction between visitor, resident and the Water Sensitive Urban Design initiatives used through out the development will be a key area of focus in the landscape. The retention of significant existing vegetation where possible will be combined with an innovative site wide planting strategy Structured planting using a combined native and exotic plant palette is proposed.

The creation of view corridors to the river precinct is seen as an integral component to the landscape and urban design philosophy. There will be an increase in biodiversity through street trees, integrated WSUD and planting to both public and private areas

The landscape design philosophy recognises, the current trends in the new home owners demographic. It is accepted that there will be a strong trend of responding to an increased community expectation of a range of active and passive recreational uses. Pedestrian and cycle movement will also be addressed to the wider landscape and surrounding communities including legible connections and cycle locking facilities. This will be in accordance with the control documents and approvals to date.

A vibrant central 3000m<sup>2</sup> contiguous open space plaza at the core of the development on the waterfront will be for passive & active recreation multi-use and adaptable for residents and public use. It is intended that this space become a place of celebration for community events, meeting people and taking advantage of the river views. A cafe integrated into the built form at this location will ensure activation so the development reaches capacity.

A Holistic approach to the landscape design combined with the careful interaction of landscape & architectural elements across the site will result in a 'big picture' design creating and reinforcing the local identity, character and sense of place.

A sensitive and appropriate standard of landscape design is to be applied to the Shepherds Bay development so that the practical, aesthetic and social needs of the residents and community are realised. Detailed design of all public domain areas are to be based on the CPTED principles for safety and security. The concept plan designs are indicative and intended as a guide to future detailed designs.



Wider Context Plan NTS



Meadowbank, Shepherds Bay Site and Stage Context Plan NTS

### DEVELOPMENT CONTROL CONDITIONS

#### LANDSCAPE / PUBLIC DOMAIN RELATED

The following development control conditions have been applied to the landscape design.

- 1(c). Provide a public domain plan which illustrates the proposed public domain treatment including streets and setback areas, landscaping, lighting and public and communal open spaces and which is in accordance with Ryde City Council's Public Domain Technical Manual
- B1(e). Provide an integrated water sensitive urban design (WSUD) strategy for the entire site.
- B1(f). Include a pedestrian and cycleways plan that demonstrates that the proposed routes are both viable and integrated with Council's plans for the surrounding area.
- 11. Landscaping: Future DAs shall include detailed landscape plans for public and private open space areas, street setbacks areas and for the landscape treatment of all adjoining public domain areas and road reserves in accordance with the approved Public Domain Plan.
- 12. Public Domain: Future DAs shall provide the detailed design for the upgrade of all road reserves adjacent to the development to the centre line of the carriageway, including landscaping, street trees, accessible pedestrian pathways, street lighting, cycle ways on Constitution Road and Nancarrow Avenue, and any other necessary infrastructure in accordance with the approved Public Domain Plan. Where the detailed design necessitates an increase in the width of the road reserve, building setbacks are to be increased to retain the approved setback to the road reserve alignment. The road reserve works are to be completed by the proponent prior to occupation of each stage.
- 15. Open Space/Public Access: Future DAs shall include detailed landscape plans for the embellishment of publicly accessible open space areas. These areas shall include high quality landscaping and paved areas and a variety of recreation facilities which may include BBQs, seating, water features, grassed areas, paths, shade trees, bicycle racks and exercise equipment/games.

16. Open Space/Public Access: Future DAs shall include detailed landscape plans which demonstrate accessible paths of travel for all persons for at least two of the northsouth routes between Constitution Road and the Foreshore with one of the routes including the Lower Riparian linear park and a second path either along the Central Spine or the public pathway associated with Stage One.

Landscape plans will also include the detailed design of at least 1 north-south cycle path linking Constitution Road through the site to the existing foreshore cycleway.

- 17. Open Space/Public Access: Future DAs shall clearly set an appropriate legal mechanism for creating rights of public access to all publicly accessible areas of open space, drainage reserves and through site links, with the relevant instrument/s to be executed prior to the issue of the occupation certificate.
- 9.8. New Lower Riparian Foreshore Link Publicly Accessible Open Space (Development Stages 8 & 9): This new publicly accessible open space will be delivered as part of Indicative Development Stages 8 & 9 7 and 9 as illustrated in the landscape plan report in annexure 10 of this PPR. This publicly accessible open space follows the natural overland flow path and terminates at the foreshore reserve. This publicly accessible open space provides more water features and soft plantings interspersed with a sequence of passive recreation lawns with specimen tree planting for shade.

The orange orchard reflects the past uses of this site and creates a desirable area to sit and relax away from the more urban landscapes to the east.

Landscape Design Principles:

- Heritage interpretation of past land use
- Natural creek like water features and plantings
- Low maintenance softscape & hardscape elements
- Temporary stormwater detention ponds and ephemeral creek beds

9.9, New Pedestrian Spine 1 (South) Publicly Accessible Open Space (Development Stage 8) This new publicly accessible open space will be delivered as part of Indicative Development Stage 8 The pedestrian

link south continues the formal character of the northern portion of this publicly accessible open space, becoming more informal closer to the foreshore reserve, with swathes of low and mid height native shrub and low maintenance hybrid grass planting. Tree planting is orchard style and is recommended in the lower portion of this publicly accessible open space, reflecting the previous orchards on the Concept Plan site while retaining clear sightlines from top to bottom.

Landscape Design Principles:


- Performs as formal linear open space in addition to its role as a pedestrian link
- Low maintenance, high quality hard cape surface treatments
- Formal modern alignment with informal garden bed design
- Incorporates heritage orchard tree planting
- Clear sight lines through the park to maximise pedestrian
- Formal water features

#### 13. Tree Management

Tree protection measures will be implemented for trees to be retained as recommended in the Arborist Report at Annexure 23 to the submitted EA.



# PEDESTRIAN + CYCLEWAY PLAN (DEVELOPMENT- WIDE)













# STREET TREE STRATEGY (DEVELOPMENT-WIDE)

# LEGEND: Corymbia maculata (Spotted Gum) Angophora costata (Sydney Red Gum) Cupaniopsis anacardiodes (Tuckeroo) Magnolia grandiflora ('Little Gem') Fraxinus griffithii (Evergreen Ash) Fraxinus oxycarpa 'Raywoodi (Claret Ash) Syncarpia glomulifera (Turpentine) Melaleuca sp. (Paperbacks) Angophora floribunda (Rough-barked apple)

The plan shows the intended tree species to be used in the development. Existing street trees will be assessed on an individual basis to retain if possible. The suitability of the species listed below will also be considered at the detailed design stage and discussed with Council.



Note: All existing street trees will be assessed in light of this plan and retained if appropriate. Ref - Ryde Public Domain Technical Manual - 5.2











#### LANDSCAPE DESIGN INTENT STATEMENT

#### journey beginning

The Central Spine is considered the beginning of the escarpment character, the journey begins at the higher end of the two sites along Constitution Road, and continues through a gradual build up in height around the main path, designed in a more softer medium and delivered through landscaped berms and terraces. An elevated walkway branches from the side of the path leading up to a higher level private communal courtyard, whilst incorporating a new story, the tree-top walk.

These elements are the beginning of a strong landscape character as well as aiding to respond to the sites level changes. They are also instrumental in the movement of water through the site, ensuring adequate depths and overland flow paths are maintained using a mixture of retaining walls, gradual falls and landscape berming, combined with water sensitinve urban design features such as bio-retention basins and dry creek beds (designed to channel water in rain periods).

#### nexus plazas / heritage responses

Where both stages of the development meet at Nancarrow Road, open plaza spaces have been proposed to ensure fluid movement is encuoraged and easy. These central plazas are anticipated to house heritage elements significant to the site, such as an 'orange orchard' within stages 8-9 and the resuse of 1950s style fencing fromt the old Automatic Totalisors Factory situated on 37 Nancarrow Road on Stage 6-7 side. (See images left)

#### 'factory fencino

The fencing available for reuse is approximately 47m in 12 sections and is antici[ated to either be further explored as part of a public art stratedy or to appear as a landscape feature within the podium open space area between building 9A-9B.

#### 'orange orchard'

The Orange Orchard is a reflective and soft landscape with bosque of Orange trees within a decomposed granite surface. Seating has been located under the orange trees and the trees themselves extend beyound the limits of the plaza, drawing the outside in and creaiting a 'leak' of history into the new developement.

#### escarpment

Moving south from Nancarrow Road plazas, the landscape becomes more severe and levels adjacent the path start to rise higher through gabion and sandstone faced walls. Materials become more 'raw' and refective of both the landscape journey and the exisitng / past industrial charachter, whilst still being modern and architectural in form.

#### rawness and architectural form

sandstone gabion walls being to move in closer to the path providing elevated rest areas and viewing spaces. Corten panels and steel i-beams integrated with both the gabion walls and into handrails on the upper level, provide a unique design element that adds to the character and style of both the architectural and landscape design.

the path continues to crossroad, where the user can travel west up towards Bowden Street over podium or south towards Rothesay Street.

podium building 9A-9B

the podium landscape is designed in the same nature as the escarpment, with a mixture of raw elements and tidier lines, still with a layering of levels and landscape to provide visual interest and zones for passive recreation

the podium has also been designed to safely carry overlaand flow from bowden street through the site and into the bioretention basins/

#### bbq area (public open space)

continuing to rothesay street, south along the cycle way, a WSUD bioretention basin is incorporated into a flexible public open space area. This area provides an undefined area for casual get-togethers or functions as well as a bbq area and seating.

It is surrounded by terraced planters to compensate dramatic level change, but is still lush with planting, providing ample greenery, shade and amenity. The bio-retention basin is accessible down a set of seating steps and contains a boarwalk feature around and over it, making it visually accessible during rain periods and accessible during dry periods.

#### residents pool

the pool area is simple in design with clean lines and architectural from + materials, whilst still ensuring a relaxing, casual zone with a high-quality 'sub-tropical' feel to it through the choice of plantings (lush hardy flowering species such as bird of paradise and gymea lily). Planting to be arranged in formal rows of minimal species. The pool is anticiapted to reflect the architectural character through reconsitututed stone, composite timber decking, ornate pool tiles as examples.

#### LANDSCAPE DESIGN DRIVERS

Performs as formal linear open space in addition to its role as a pedestrian link

- Incorporates formal avenue tree planting as a way of screening the adjoining existing building
- Includes clear sight lines through the open space to maximise pedestrian safety
- Includes large reflection pond/water body
- The provision of an easy, safe and enjoyable pedestrian connection with peaceful places to stop and relax
- Optimise ecological functionality through planting of endemic species
- Incorporate overland flow paths into water features within the publicly accessible open space
- Combined active and passive recreation spaces
- Provision of contemplative lawns with shade

## STAGES 6-7 + 8-9 COMBINED MASTERPLAN

## STAGES 6-7 + 8-9 MASTERPLAN





## street trees at typ 8m centres as per ryde public domain technical bioretention pods as per ryde — public domain technical manual manual linkage across nancarrow avenue loading bay carpark entrance to building 8 carpark 'Orange Orchard Plaza' -Garbage buggy access route from building 8 to 9A Orange orchard reflecting past usage of site with heritage information plaque small retaining wall to creek bed level to compensate for level change · linear dry creek bed (WSUD) flowing to bioretention area within public open space area planted with swathes of native grasses angled sandstone gabion walls-with integrated steel I-beam sections and corten panels bridge over dry creek bed to elevated landscape zone Garbage buggy access route from building 8 to 9A angled sandstone gabion walls with integrated steel I-beam sections and corten panels, handrail integrated into I-Beam feature large turfed public open space sandstone blockwork walls areas upper level terraces planted terraces up to upper level handrail formal water feature timber boardwalk and bridge over dry creek bed to public bbq area terraced planters up to podium level seating steps to lower turf level bio-retention basin RL 4.650 1:20 access paths to podium level landscape berms elevated timber platform down to path access path to building 9B

LANDSCAPE PLAN | THE ESCARPMENT: PRIMARY SITE LINK

Scale 1:350 @ A3

## THE ESCARPMENT / CENTRAL SPINE















# THE ESCARPMENT / CENTRAL SPINE





## PUBLIC OPEN SPACE/PRIVATE OPEN SPACE BUILDING 8






Scale 1:350 @ A3


## 4

# PUBLIC OPEN SPACE/PRIVATE OPEN SPACE BUILDING 8









joins right







# EAST SITE LINK BUILDING 8 / STAGE 3 + ADJACENT PROPERTY





## NANCARROW ROAD FRONTAGE


## Streetscape Design Philopsphy

Street trees throughout the site will be reflective of the Meadowbank street tree master pla.n The street tree design to the site is intended to enhance strong legible links, providing biodiversity and aesthetic consistency across the site, both in streetscapes and site through links.

The planting will reference the DCP, Council Public Domain Technical Manual and Council guidelines.

Refer to WSUD doucment for detail on rain gardens. The design of raingardens will be to Ryde city council specifications and in line with Ryde city council maintenance plan.






Grey banding as per — the Ryde Public Domain Row of Angophora floribunda — Loading Bay in 1.5m x 1.5m grey resin-Technical Manual bound gravel treepits as Rain Gardens as per per the Ryde Public Domain Technical Manual the Ryde Public Domain Technical Manual 2.5m wide cycleway Additional nativelow planting Crossing between Carparks as per the Rydeproposed to Stages 6-7 + 8-9 Public Domain Technical buildouts nancarrow road


SCALE 1:50 @ A3

## STAGE 8-9 STREETSCAPES: BOWDEN STREET TYPICAL






Section E
Typical Private/Streetscape Interface
Scale 1:100 @ A3



Shepherds Bay - Typical Street Section (All Other Streets) - Bowden Street Ryde City Council Guidelines

Ref - Ryde Public Domain Technical Manual - 5.2



## STAGE 6-7 TREE / SOFTSCAPE STRATEGY

GENERAL TREE MIX (Native + Exotic) (Public Open Space + Residential)

Cupaniopsis anacardiodes - Tuckeroo Elaeocarpus reticulatus - Blueberry Ash Ficus macrophylla - Moreton Bay Fig Fraxinus griffithii - Evergreen Ash Fraxinus oxycarpa - 'Raywood' Claret Ash Lagerstroemia indica - Crepe Myrtle Lagerstroemia speciosa - Giant Crepe Myrtle Lagerstroemia indica fauriei - Crepe Myrtle Acoma Lophostemon confertus - Brush Box Pistascia chinensis - Chinese Pistache Plantus x Hybrida - Chinese Tallwood 'yrus calleryana 'Chanticleer' - Manchurian Pear apium serbiferum - Chinese Tallowood Ulmus parvifolia - Chinese Elm Waterhousia floribunda - Weeping Lily Pily



PALMS (Public Open Space + Residential)

Archontophoenix Cunninghamiana - Bangalow Palm Archontophoenix alexandrae - Alexandra Palm Livistona australis - Cabbage Tree Palm Phoenix canariensis - Canary Palm

NATIVE TREES (Public Open Space + WSUD)

Angophora costata - Sydney Red Gum Angophora floribunda - Rough-Barked apple Cupaniopsis anacardiodes - Tuckeroo Corymbia Maculata - Spotted Gum Elaeocarpus reticulatus - Blueberry Ash Ficus macrophylla - Moreton Bay Fig Lophostemon confertus - Brush Box Melaleuca species - Paperbarks Syncarpia glomulifera - Turpentine Tristaniopsis laurina - Water Gum Waterhousia floribunda - Weeping Lily Pily



FEATURE TREES (Public Open Space)

STREET TREES

Ficus macrophylla = Moreton Bay Fig Magnolia grandiflora 'Little Gem' - Magnolia

(Locations as indicated on plans)

Angophora costata - Sydney Red Gum

Fraxinus oxycarpa - 'Raywood' Claret Ash

Angophora floribunda - Rough-Barked apple

Magnolia grandiflora - 'Little Gem'

Syncarpia glomulifera - Turpentine

HERITAGE TREES

Citrus x sinensis - Orange Tree

Fraxinus griffithii - Evergreen Ash



**TURF** 






WSUD PLANTING MIX Native Species Only (see indicative planting schedule)



RETAINED TREES

See aborist report



STAGE 6-7 PLANTING STRATEGY

The Planting palette to be used throughout the site has been selected for it's suitability to fulfill the following criteria:

- Enhance the local character of Meadowbank
- Create a new defined precinct
- Remain in line with the City of Ryde's environmental policies
- Soften and visually reduce bulk/scale of built forms
- Provide buffering/screening to residential areas
- Contribute to habitats of the local fauna
- Minimise potable water use in the landscape

A wide selection of trees, both native and exotic, have been selected for the sites streetscapes and landscaped areas. Where possible local natives will be used to remain consistent with the vegetation communities found within the City of Ryde. Specific areas will see exotic species used for accent planting and foliage interest

Shrubs have been chosen not only for their aesthetic attributes but also functionality in terms of providing buffering and screening to residential precincts. Lush foliage and dense growing habits have been favoured.

Grasses and groundcovers have been selected from a predominantly native palette and will be aimed at softening edges and large areas of hardscape.











## STAGE 6-7 INDICATIVE PLANTING SCHEDULE

## Streetscape Trees

Botanical Name	Common Name	Height + Spread (h x w)	Container Size	plants per m2
Angophora costata	Sydney Red Gum	20.0m x 8.0m	75L	As Shown
Magnolia grandiflora	'Little Gem'	4.0m x 3.0m	75L	As Shown
Fraxinus griffithii	Evergreen Ash	6.0m x 4.0m	75L	As Shown
Fraxinus oxycarpa	'Raywood' Claret Ash	12.0m x 12.0m	75L	As Shown
Syncarpia glomulifera	Turpentine	20.0m x 8.0m	75L	As Shown
Angophora floribunda	Rough-Barked apple	20.0m x 8.0m	75L	As Shown

## General Planting

Botanical Name	Common Name	Height + Spread (h x w)	Container Size	plants per m2
TREES				
EVERGREEN				
Angophora costata	Smooth Barked Apple	20.0m x 8.0m	75L	As Shown
Corymbia maculata	Spotted Gum	30.0m x 15.0m	75L	As Shown
Cupaniopsis anacardioides	Tuckeroo	8.0m x 8.0m	75L	As Shown
Elaeocarpus reticulatus	Blueberry Ash	10.0 x 7.0m	75L	As Shown
Ficus macrophylla	Moreton Bay Fig	30.0m x 20.0m	75L	As Shown
Fraxinus ornus	Meczek	20.0m x 10.0m	75L	As Shown
Lophostemon confertus	Brush Box	10.0m x 12.0m	75L	As Shown
Tristaniopsis laurina 'Luscuious'	Water Gum	12.0m x 8.0m	75L	As Shown
Waterhousia floribunda	Weeping Lily Pily	12.0m x 8.0m	75L	As Shown
PALMS				
Archontophoenix cunninghamiana	Bangalow Palm	25.0m x 3.0m	200L	As Shown
Archontophoenix alexandrae	Alexandra Palm	30.0m x 2.0m	200L	As Shown
Livistona australis	Cabbage Tree Palm	25.0m x 3.0m	400L	As Shown
Phoenix canariensis	Cabbage Tree Pairii  Canary Palm	25.0m x 3.0m	400L 400L	As Shown
DECIDUOUS	Cariary Fairi	TO.OHT & O.OHT	400L	AS SHOWIT
Acer platanoides	Dosignor Manlo (Clohosum)		200L	As Shown
Acer piatanoides Acer palmatra	Designer Maple 'Globosum' Osakazuki		200L 200L	As Shown As Shown
Lagerstroemia indica: Lipan:		4.0m x 3.0m	200L 200L	As Shown
<u> </u>	Crepe Myrtle Giant Crepe Myrtle	3.0m x 3.0m	200L 200L	As Shown
Lagerstroemia speciosa				As Shown
_agerstroemia indica fauriei	Acoma	8.0m x 6.0m	400L	
Pistascia chinensis	Chinese Pistache	10.0m x 4.0m	75L 75L	As Shown As Shown
Plantus x Hybrida	Plane Tree	20.0m x 9.0m	75L	
Pyrus calleryana 'Chanticleer'	Manchurian Pear	11.0m x 6.0m	75L	As Shown As Shown
Sapium sebiferum	Chinese Tallowood	8.0m x 4.0m	75L 75L	
Ulmus parvifolia	Chinese Elm	14.0m x 10.0m	/5L	As Shown
FEATURE TREES	0	0.0/	4001	A = Cl= =
Citrus x sinensis	Orange	9.0m x 6.0m	400L	As Shown
Ficus macrophylla	Moreton Bay Fig	35.0 x 25.0m	400L	As Shown
Magnolia grandiflora 'Little Gem'	Magnolia	4.0m x 3.0m	400L	As Shown
SHRUBS + ACCENT				
	Sudney Creen Mettle	4.0m ;; 2.0m	251	Ac Charre
Acacia parramattensis	Sydney Green Wattle	4.0m x 3.0m	25L	As Shown
Acacia falcata	Sickle-shaped Acacia	4.0m x 1.5m	25L	As Shown
Banksia serrata	Dwarf Bottlebrush	2.0m x 2.0m	5L	4/m2
Cordyline australis	Sunrise	3.0m x 1.0m	25L	As Shown
Cordyline sp	Cordyline	3.0m x 1.0m	25L	As Shown
Dodonaea triquetra	Hop Bush	3.0m x 2.0m	300mm	4/m2
Dodonaea viscosa 'Purpurea'	Hop Bush	3.0m x 1.5m	300mm	4/m2
Doryanthes excelsa	Gymea Lily	1.5m x 1.5m	25L	1/m2
Gardenia augusta 'Florida'	Gardenia	1.2m 1.0m	25L	4/m2
Kunzea ambigua	Tick Bush	5.0m x 5.0m	300mm	As Shown
Murraya paniculata	Orange Jessamine	3.0m x 3.0m	25L	As Shown
Philodendron 'Xanadu'	Xanadu	1.5m x 1.5m	200mm	5/m2
Strelitzia reginae	Bird of Paradise	1.5m x 1.0m	300mm	3/m2
Syzygium sp.	Lilly Pilly	Varies	25L	2/m2
Viburnum odoratissimum	Sweet viburnum	4.0m x 4.0m	25L	1/m2
Westringia fruticosa 'Zena'	Costal Rosemary	1.0m x 1.3m	300mm	4/m2

Botanical Name	Common Name	Height + Spread (h x w)	Container Size	plants per m2
GROUNDCOVERS /	GRASSES			
Altenanthera dentata	Blood Leaf Irisene	40mm x 90mm	200mm	5/m2
Dichondra repens	Kidney Weed	150mm x 500mm	200mm	3/m2
Dianella 'Breeze'	Paroo Lily	300mm x 300mm	200mm	4/m2
Dianella 'Little Jess'	Paroo Lily	400mm x 600mm	140mm	4/m2
Dianella 'Silver Streak'	Paroo Lily	500mm x 400mm	140mm	4/m2
Gazania hybrida	Gazania Double Gold	300mm x 300mm	200mm	5/m2
Hardenbergia 'Purple Spray'	Native Violet	1.5m x 2.0m	200mm	2/m2
Hibbertia scandens	Snake Vine	3.0m x 3.0m	200mm	2/m2
Isolepis nodosa	Club Rush	500mm x 300mm	140mm	4/m2
Juncus usitatus	Common Rush	500mm x 300mm	140mm	4/m2
Liriope 'El Marco'	Turf Lily	150mm x 400mm	140mm	4/m2
Lomandra hystrix	Mat Rush	0.6m x 1.0m	140mm	4/m2
Lomandra longifolia 'Tanika'	Mat Rush	600mm x 650mm	200mm	4/m2
Poa labillardieri 'Eskdale'	Tussock Grass	800mm x 400mm	200mm	4/m2
Scaevola aemula	Fairy Fan-flower	0.2m x 1.5m	200mm	4/m2
Trachelospermum jasminoides	Star Jasmine	0.4m x 1.5m	200mm	4/m2

## WSUD (Dry Creek Bed + Bio-retention)

Botanical Name	Common Name	Height + Spread (h x w)	Container Size	plants per m2
TREES / PALMS				
Ficus macrophylla	Moreton Bay Fig	30.0m x 20.0m	75L	As Shown
Corymbia maculata	Spotted Gum	30.0m x 15.0m	75L	As Shown
Lophostemon confertus	Brush Box	10.0m x 12.0m	75L	As Shown
Tristaniopsis laurina 'Luscuious'	Water Gum	12.0m x 8.0m	75L	As Shown
Livistona australis	Cabbage Tree Palm	25.0m x 3.0m	400L	As Shown
Waterhousia floribunda	Weeping Lily Pily	12.0m x 8.0m	75L	As Shown
GROUNDCOVERS /	GRASSES			
Dianella 'Breeze'	Paroo Lily	300mm x 300mm	200mm	4/m2
Dianella 'Little Jess'	Paroo Lily	400mm x 600mm	140mm	4/m2
Dianella 'Silver Streak'	Paroo Lily	500mm x 400mm	140mm	4/m2
Isolepis nodosa	Club Rush	500mm x 300mm	140mm	4/m2
Juncus usitatus	Common Rush	500mm x 300mm	140mm	4/m2
Liriope 'El Marco'	Turf Lily	150mm x 400mm	140mm	4/m2
Lomandra hystrix	Mat Rush	0.6m x 1.0m	140mm	4/m2
Lomandra longifolia 'Tanika'	Mat Rush	600mm x 650mm	200mm	4/m2

Note: The term 'as shown' denotes need to place individual plant species for desired landscape outcomes

## STAGE 8-9 STREETSCAPE STRATEGY

NOTE: STREETSCAPES WILL BE DESIGNED EXACTLY IN ACCORDANCE WITH THE RYDE CITY COUNCIL PUBLIC DOMAIN MANUAL

## Design Intent

The Shepherds Bay Streetscape Character and Tree Species will reflect the character of the site whilst accommodating for the requirements of Council. The functional needs of pedestrians, cyclists and vehicular movements will also be paramount in the design of vehicular carriage ways.

The streetscape character will generally reinforce and enhance the road hierarchy to create subtle but distinctive streetscape precincts. The formal planting of mid to large size trees on Primary Local Roads (Dependant on Council approval) and the introduction of smaller native species on Secondary Local Roads will occur. A combination of both native and hybrid indigenous trees must dominate the selection of street trees to the internal roads.

Streets are to be designed to provide an appropriate level of on street parking with priority given to pedestrians and cyclists to provide a pleasant environment to promote walking and social activity.

Some key points are listed below;

#### Aspect and Views

- Strong visual associations with existing vegetation communities both native and cultural.
- Use of Landmark species to clearly identify entry points into the development.
- Strong emphasis to avenue planting with spacings of trees to enable canopies to touch when trees are mature.

#### Accessibility

- Continuity of streetscape character and connectivity to local and recreational paths linking the entire site.

#### Materials:

- Pathways will predominantly be robust contemporary materials such as exposed aggregate concrete. All driveway cross overs are to be of the same material in order to ensure visual continuity.

#### Plantings:

- Maximise landscaping in all streets while tailoring species selection to that of the local and site context.
- Preservation of plantings of culturally significant species to enhance the historic 'sense of place'
- Canopy trees to provide shade and visual amenity.
- Low shrub and groundcover planting using a mix of low maintenance plant species

#### Safety:

- All street trees will be carefully selected so that the pedestrian sight lines are well maintained.
- Street lighting and feature lighting will also be carefully designed to meet the safety criteria for pedestrian/cycle and car links.

#### Indicative Materials + Elements

**BOWDEN STREET** 

Carriageway Thresholds 100 x 100 x 60mm Australian Porphyry Stone

Tree Pits

1500mm x 1500mm resin bound gravel (grey colour)

Banding

300 x 300 x 60mm Grey Granite Banding

Paving

600 x 300 x 60mm Grey Granite Paving and 300 x 300 x 60mm Grey Granite Paving

Lighting

Smart Poles at 9.6m spacings (between trees)

Trees

8m Spacings

Tree Species

Fraxinus griffithii (evergreen ash)

Fraxinus griffithii oxycarpa (Raywoodi) Claret Ash

#### NANCARROW ROAD

Carriageway Thresholds

100 x 100 x 60mm Australian Porphyry Stone

Tree Pit

1500mm x 1500mm resin bound gravel (grey colour)

Banding

300 x 300 x 60mm Grey Granite Banding

Paving

600 x 300 x 60mm Grey Granite Paving and 300 x 300 x 60mm Grey Granite Paving

Lighting

Smart Poles at 9.6m spacings (between trees)

Rain Gardens

To council specifications

Trees

8m Spacings

Tree Species

Northern Verge (6-7 Frontage) Angophora floribunda (Rough-barked Apple) Southern Verge (8-9 Frontage) Magnolia grandiflora ('Little Gem')

## Indicative Tree Palette + Planting Character



Nancarrow Road Northern Verge (6-7 Frontage) Angophora floribunda (Roughbarked Apple)



Nancarrow Road Southern Verge (8-9 Frontage) Magnolia grandiflora ('Little Gem')



Indicative character where additional planting is proposed

## STAGE 8-9 TREE RETENTION / REMOVAL STRATEGY



## STAGE 8-9 LANDSCAPE MATERIALITY

Indicative Materials Palette: Streetscape Selected images from Ryde Public Domain Technical Manual + Place Design Group





































## STAGE 8-9 MATERIALS STRATEGY




#### Indicative Pavement Schedule

- P1 Standard concrete to shared 2.5m wide cycleway (as per Ryde Public Domain Plan) + general pedestrian paths
- P2 Precast high quality concrete/limestone pavers with sandstone porphyry banding and header
- P3 Decomposed Granite (not used in this stage)
- P4 Mixed colour sandstone paving to private courtyards 600x300x60mm
- P5 Limestone (High Quality) Pool Area (not used in this stage)
- P6 Reconstituted timber deck
- P7 Streetscape: Grey granite / limestone pavers 600x300x60 + 300x300x60mm (Ryde PDTM)
- P8 Streetscape: Australian porphyry stone on threshold 100x100x60mm (Ryde PDTM)
- P9 Resin bound gravel to base of trees (as per Ryde Public Domain Plan)

#### Indicative Walling Schedule

- W1 Sandstone clad walls (height varies) generally used for retaining walls + planters
- W2 Insitu/ Precast white concrete wall (generally used as seating steps to turf planters)
- W3 Sandstone Gabion Walls (not used in this stage)








Type 2: Banding Stone Porphory Cobbles Colour: Grey Finish: Split Sheet Size: 300x300x12mm

Length Varies

**Example of P2 pavement treatment:** Precast high quality concrete/limestone













Type 3: Feature Banding Stone Type: Porphory Setts Size: 100x100x20-40mm Finish: Sandblasted

**Example of P4 pavement treatment:** Mixed colour sandstone paving to private

## STAGE 8-9 LIGHTING STRATEGY





#### Pedestrian & Vehicular Lighting Street lighting

Mounted on 9.6m multifunction poles to Council approval. Finish on poles to match existing poles in Belmore Street. Poles to be provided with 1.5m banner arm, Rexel Optispan Aeroscreen luminaries complete with low loss ballasts and PE cells, and metal halide lamps.



#### Pedestrian/park lighting

For areas such as shared bikeway/pedestrian pathways and plazas. Mounted on 4.8 m SmartpolesTM or approved equivalent. BEGA-8081 luminaires and metal halide lamps.



#### Solar lighting for parks (\* Courtyards)

Supplier: Solar G

Pole: galvanised utility pole

Light fittings: "Streetwalker" on 1metre outreach arm Lamps: 2x 14W fluorescent (T5 fluorescent technology, 96

Note: Due to the lack of sunlight in some areas we will propose a different fitting/light pole



#### Feature columnar Lighting

Supplier: Bega Light structure: 2.5 high aluminium linear element with white acrylic diffuser. IP65

Lamps: 151.2W LED

NOTE: Diagram is a strategy only, and is dependant on future detail design for specific information on products and locations

## STAGE 8-9 FURNITURE STRATEGY

Bins (Bin 1)

Council's standard double bin.

Bollards (Bollard 4) 1300mm high x 150mm dia 1.6mm thick 316 stainless steel Core drilled to depth of 400mm. Colorfen Constructions Ph (02) 9545 4284

Seating Bespoke seating elements (concrete

Urban Seat 11 (aluminium) Botton and Gardiner urban furniture ph (02) 9667 8100

Bicycle Racks Environ Bike Racks ENV09 Urban Art Projects

Heritage Fencing (Resued from site)

Ref: City of Ryde Public Domain R+Technical Manual - 5.2

NOTE: Diagram is a strategy only, and is dependant on future detail design for specific information on products and locations



## STAGE 8-9 ROOFTOP GARDEN STRATEGY







#### BENEFITS OF RELOCATABLE ROOFTOP PLANTERS

- containers are movable
- no set down
- suitable weight bearing structure not needed







appendices

# HARRIS PAGE & ASSOCIATES SHEPHERDS BAY **STAGES 8 & 9** STORMWATER CONCEPT DESIGN

## STORMWATER SERVICES LEGEND

#### **GENERAL NOTES**

- 1. DRAWINGS ARE DIAGRAMMATIC ONLY AND HAVE BEEN PREPARED FOR THE PURPOSE OF INDICATING
- DRAWINGS ARE DUAGRAMMATIC ONLY AND HAVE BEEN PREPARED FOR THE PURPOSE OF INDICATING THE DESIGN NITEM TAN SOCPOE OF WORKS OF THE HYDRAULD SERVICES.
   IT IS THE RESPONSIBILITY OF THE BUILDER ANDIOR PLUMBING SUBCONTRACTOR TO INVESTIGATE AND COORDINATE BEFORE AND DURING THE CONSTRUCTION PHASE ALL EXISTING SERVICES WHICH WILL EFFECT THE INSTALLATION OF THESE SERVICES.
   HYDRAULIC DRAWINGS ARE TO BE READ IN CONJUNCTION WITH THE HYDRAULIC SERVICES SPECIFICATION AND WITH RELEVANT ARCHITECTURAL, STRUCTURAL, MECHANICAL AND ELECTRICAL
- 4. ALL WORK TO BE CARRIED OUT IN ACCORDANCE WITH THE RELEVANT CODES AND AUSTRALIAN
- AND ARE TO BE CHECKED PRIOR TO COMMENCING ANY WORK.

  DO NOT SCALE FROM THIS DRAWING, REFER TO ARCHITECTURAL DRAWINGS FOR DIMENSION


#### ABBREVIATIONS


A/B	ABOVE	MM	MILLIMETERS
@	AT	N.T.S	NOT TO SCALE
BDO	BALCONY DRAINAGE OUTLET	O/F	OVER FLOW
CIS	CAST IN SLAB	%	PERCENTAGE
CO	CLEAROUT	PDO	PLANTER DRAIN OUTLET
CONT	CONTINUATION	RL	REDUCED LEVEL
D	DEPTH	RWR	RAINWATER RE-USE
DIA	DIAMETER	RWO	RAINWATER OUTLET
DP	DOWNPIPE	RV	REFLUX VALVE
е	EXISTING	SRM	SEWER RISING MAIN
H/L	HIGH LEVEL	SS	SUB SOIL DRAINAGE
IL	INVERT LEVEL	S/STEEL	STAINLESS STEEL
KIP	KERB INLET PIT	SSRM SUB	SOILRISING MAIN
L	LITRE	STW	STORMWATER
L/L	LOW LEVEL	SV	STOP VALVE
L/s	LITRES PER SECOND	SWP	STORMWATER PIT
m	METRES	SWRM	STORMWATER RISING MA
MAX	MAXIMUM	U/S	UNDERSIDE
MIN	MINIMUM	UV	ULTRA-VIOLET

#### DRAWING SCHEDULE

DWG No.	Scale	Drawing Title		
SW-00	NTS	STORMWATER SERVICES COVER SHEET AND LEGEND		
SW-01	1:500	STORMWATER SERVICES SEDIMENT & EROSION CONTROL PLAN		
SW-02	1:250	STORMWATER SERVICES BASEMENT LEVEL 5		
SW-03	1:250	STORMWATER SERVICES BASEMENT LEVEL 4		
SW-04	1:250	STORMWATER SERVICES BASEMENT LEVEL 3		
SW-05	1:250	STORMWATER SERVICES BASEMENT LEVEL 2		
SW-06	1:250	STORMWATER SERVICES BASEMENT LEVEL 1		










turner




SHEPHERDS BAY STAGE 8 & 9


STORMWATER SERVICES COVER SHEET, LEGEND & NOTES

OCT. 2014	AT	TN		NTS @B
PROJECT No. 5728	SW-00			P1










COPYRIGHT OF HARRE ASSOCIATES
Ply Ltd. All rights neserved. This drawing may not be
reasen in part or in whole without permission from
HARRIS PAGE ASSOCIATES Ply 1 Mr. for dimensions shall be taken for the contraver.



#### EROSION & SEDIMENT CONTROL

- THIS PLAN TO BE READ IN CONJUNCTION WITH THE ARCHITECTURAL AND ENGINEERING PLANS AND ANY OTHER PLANS OR WRITTEN INSTRUCTIONS THAT MAY BE ISSUED


- 1) INSTALL ANY NECESSARY SECURITY/BOUNDARY FENCES FOR THE SITE
  2) CONSTRUCT "SILT" FENCING AS DETAILED ALONG DOWNSLOPE BOUNDARY
- DURING WINDY WEATHER, LARGE UNPROTECTED AREAS SHALL BE KEPT MOIST (NOT WET) BY SPRINKLING WITH WATER TO KEEP DUST UNDER CONTROL.
- FINAL SITE LANDSCAPING SHALL BE UNDERTAKEN AS SOON AS POSSIBLE, AND WITHIN TWENTY WORKING DAYS FROM COMPLETION OF CONSTRUCTION ACTIVITIES.
- SAND USED IN THE CONCRETE CURING PROCESS SHALL BE REM AND WITHIN TEN WORKING DAYS FROM PLACEMENT.
- TEMPORARY SOIL AND WATER MANAGEMENT STRUCTURES SHALL BE REMOVED ONLY AFTER THE LANDS THEY ARE PROTECTING ARE REHABILITATED.
- THE CONTRACTOR SHALL PROVIDE ACCEPTABLE RECEPTORS FOR CONCRETE & MORTAR SLURRIES, PAINTS, ACID WASHINGS, LIGHT-WEIGHT WASTE MATERIALS AND LITTER AS REQUIRED.

- REMOVE TEMPORARY SOIL CONSERVATION STRUCTURES AS A LAST ACTIVITY
  IN THE REHABILITATION PROGRAMME.





····





turner


Lord 1, 410 Crown Street T +61 2 8668 0000 Sany Hills NSW 2010 F +61 2 8668 0068 Australia terrentiadio-com-su



SHEPHERDS BAY STAGE 8 & 9

STORMWATER SERVICES SEDIMENT & EROSION CONTROL PLAN

	OCT. 2014	AT	TN		1:500 @1
5/28   5VV-U1   PT	PROJECT No. 5728	SW-01		P1	




- THE STORMWATER DRAINAGE IS DESIGNED IN CONJUNCTION WITH CARDNO WSUD MASTER PLAN DOCUMENT 600283, WSUDMASTERPLANREPORTIVEZ DATED 24/04 /20/13 & RYDE CITY COUNCILS DEVELOPMENT CONTROL PLAN 20/10 SECTION 8.
  ALL DRAININGS TO BE READ IN CONJUNCTION WITH BGBE STORMWATER ROAD INFRASTRUCTURE DRAININGS FOR CONNECTIONS TO BIO-RETENTION AREAS AND INFRASTRUCTURE TRUNK MAIN
- ALL ARI(AVERAGE RECURRENCE INTERVALS) & RAINFALL INTENSITY DATA ARE BASED FROM INFORMATION COLLECTED FROM THE 'BUREAU OF METEOROLOGY'.

AVERAGE RECURRENCE INTERVALS (MEADOWBANK) 20YR - 186MM/HR 50YR - 215MM/HR 100YR - 238MM/HR

4. THE 'RATIONAL METHOD' HAS BEEN ADOPTED FOR ALL SITE CATCHMENTS CALCULATIONS.

- 100% OF EACH BUILDING ROOF AREA ASSUMED TO BE NON TRAFFICABLE AND DISCHARGE TO ASSOCIATED RAINWATER TANKS.
  ALL ANDSCAP AREA TO DISCHARGE TO NOTED BIO-RETENTION FILTRATION BASIN BIO RETENTION FILTRATION BASIN TO BG&E DESIGN DETAILS.





LECEND	
LEGEND	

---- CATCHMENT ZONE SUBSOIL DRAINAGE LINE

> STORMWATER PIT

300mm<sup>2</sup> GRATED OUTLET

STORMWATER HEADWALL

0 DOWNPIPE CLEAR OUT 

BIO-RETENTION AREA






turner



SHEPHERDS BAY STAGE 8 & 9

DA SUBMISSION STORMWATER CONCEPT BASEMENT LEVEL 5

DATE	DRAWN	CHECKED	No IN SET	SCALE
OCT. 2014	АТ	TN		1:200 @E
PROJECT No.	DRAWING No.			REVISION
5728	SW-02			P1
(				



#### GENERAL NOTES

- THE STORMWATER DRAINAGE IS DESIGNED IN CONJUNCTION WITH CARDINO WSUD MASTER PLAN DOCUMENT 500283, WSUDMASTERPLANREPORTIVEZ DATED 24/04 /2013 & RYDE CITY COUNCILS DEVELOPMENT CONTROL PLAN 2010 SECTION 8.
  ALL DRAWINSS TO BE READ IN CONJUNCTION WITH BGBE STORMMATER ROAD INFRASTRUCTURE DRAWINGS FOR CONNECTIONS TO BIO-RETENTION AREAS AND INFRASTRUCTURE TRUNK MAIN
- DESIGN.


  ALL ARI(AVERAGE RECURRENCE INTERVALS) & RAINFALL INTENSITY DATA ARE BASED FROM INFORMATION COLLECTED FROM THE BUREAU OF METEOROLOGY.

AVERAGE RECURRENCE INTERVALS (MEADOWBANK) 20YR - 186MM/HR 50YR - 215MM/HR 100YR - 238MM/HR

- 4. THE 'RATIONAL METHOD' HAS BEEN ADOPTED FOR ALL SITE CATCHMENTS CALCULATIONS.
- 100% OF EACH BUILDING ROOF AREA ASSUMED TO BE NON TRAFFICABLE AND DISCHARGE TO ASSOCIATED RAINWATER TANKS.

  ALL LANDSCAPE AREA TO DISCHARGE TO NOTED BIO-RETENTION FILTRATION BASIN. BIO RETENTION
- FILTRATION BASIN TO BG&E DESIGN DETAILS.





ï	=	-	N.I	n
_	=	∍⊏	IN	$\boldsymbol{\nu}$

---- CATCHMENT ZONE SUBSOIL DRAINAGE LINE STORMWATER DRAINAGE LINE

> STORMWATER PIT

300mm<sup>2</sup> GRATED OUTLET


STORMWATER HEADWALL

DOWNPIPE 0

CLEAR OUT 



BIO-RETENTION AREA





## turner

Lord 1, 410 Crown Street T +61 2 8668 0000 Sany Hilla NSW 2010 F +61 2 8668 0068 Australia terrentadio-com-su





SHEPHERDS BAY STAGE 8 & 9

DA SUBMISSION STORMWATER CONCEPT BASEMENT LEVEL 4

5728	(	SW-03		P1
PROJECT No.	D	RAWING No.		REVISION
OCT. 2014	AT	TN		1:200 @I
DATE	DRAWN	CHECKED	No IN SET	SCALE







LEGEND

----- CATCHMENT ZONE
SUBSOIL DRAINAGE LINE
STORMWATER DRAINAGE LINE

STORMWATER PIT

300mm² GRATED OUTLET


STORMWATER HEADWALL

DOWNPIPE

CLEAR OUT



BIO-RETENTION AREA





ARCHITECT / PROJECT MANAGER

**EUFNES**Level 1, 410 Crown Street
Sarry-Ha NSW 2010
Autholo


AULIC & FIRE SERVICES CONSULTANTS




SHEPHERDS BAY STAGE 8 & 9

DA SUBMISSION
STORMWATER CONCEPT
BASEMENT LEVEL 3

PROJECT No. 5728	DRAWING No. SW-04		REVISION P1	
OCT. 2014	AT	TN		1:200 @B
DATE	DRAWN	CHECKED	No IN SET	SCALE







LEGEND

CATCHMENT ZONE
SUBSOIL DRAINAGE LINE
STORMWATER DRAINAGE LINE

STORMWATER PIT


300mm² GRATED OUTLET

STORMWATER HEADWALL

DOWNPIPE

CLEAR OUT

BIO-RETENTION AREA



HOLDMARK
Sute 22-4 Giffnok Avenue, Macquarie Park NSW Australia 2113
Telephone (IQ2) 9899 5540 Fax (IQ2) 9898 5829

ARCHITECT / PROJECT MANAGER

turner



SHEPHERDS BAY STAGE 8 & 9

DA SUBMISSION
STORMWATER CONCEPT
BASEMENT LEVEL 2

