


REDUCTION in shad owfrom approved building envelope

 Outline of shadow cast by Stage 6+7 - - Outline of shadow cast by approved building envelope





June 21 st 12pm 1:1000



June 21st 3pm 1:1000 3

BRIBBARINO B THE COMPACIFIED TRANSLAD INFOCRECTION CONTRIBUTION UNLESSANCE O HEADERS FOR EAST AND ENTRY OF COMPACIFIED TO THE C


SHEPHERDS BAY - STAGE 6 & 7
Nancarrow Ave, Meadowbank NSW 2114 Australia


Shadow Diagrams Winter Shadow Diagrams


14005 Drawn ky North
AC.JF. CM
Rev 14005 Dug No. A-DA-720-010

turner


Level 1, 410 Crown Street Suny Hills MSCJ 2010 Australia













ROTHESAY AVENUE DEVELOPMENTS P/L

NATURAL CROSS VENTILATION

SOLARACCESS TO LIVING AREA MINIMUMOF 2 HOURS BETT/ EEN9am -3pm NATURAL VENTILATION - VENTICAL SHAFT
NATURAL VENTILATION - CROSS OVER HORDONDAL SHAFT
NATURAL VENTILATION - CROSS OVER HORDONDAL SHAFT
NATURAL VENTILATION - CROSS OVER HORDONDAL SHAFT IMPROVED AMENITY IN ACCORDANCE UTH STSU Condition 21(c) SILL SILYLIGHT

SHEPHERDS BAY - STAGE 6 & 7 Nancarrow Ave, Meadowbank NSW 2114 Australia Ammenity Diagrams

14005 Drawn ky Nom
AC. JF. CM
Rev Dug No. A-DA-730-010

turner

DLCS Quality Endorsed Company BD >>> 12>>> , Licence Number 45>> Nominated Architect Nicholan Tumer 44>5 , ABN 44>44>44>11







3 Level 07

Level 08 (Mezzanine)

HTGGT TARRIER NO REPRODUCTION CHROUTFREAMEDON, UNASSEANCES O MERCINE THE COMMENSION TO THE COMMENSION

LEGEND - APARTMENT AMENITY

NATURAL CROSS VENTILATION

NATURAL VEHTILATION - VEKTICAL SHAFT

NATURAL VEHTILATION - CROSS OVER NO REDUTAL SHAFT

NATURAL VEHTILATION - CROSS OVER NO REDUTAL SHAFT

MINIMARY SHOWS SETVICENS AND S ■ IMPROVED AMENITY INACCORDANCE DITH STSU Condition 2 %(c) SKL SITYLGHT

SOLAR ACCESS TO LIVING AREA MINIMUM OF 2 HOURS BETT/ EEN/ham - 3pm


SHEPHERDS BAY - STAGE 6 & 7 Nancarrow Ave, Meadowbank NSW 2114 Australia DissubgTitle
Ammenity Diagrams


H 05/01/15 JF DA-Council
Rev. Date Represently Resistion Notes
1:500 @A1, 5096@A3 Propertito
Days No.
A-DA-730-020 14005 Drawn by North Rev

turner

Level 1, 410 Crown Street Surry Hills NSC/ 2010 Australia

D LCS Quality Environed Company BD 9++12++1, Licence Number 44+4 Nominated And Net (Noticine Tamer 44+5, ABN 44+44+44+11





LEGEND:



*** Proposed Building Envelope excludes Facade articulation & roof overhangs

Projectible
SHEPHERDS BAY - STAGE 6 & 7
Nancarrow Ave, Meadowbank NSW 2114 Australia

Description

Envelope Comparison Diagrams

Stage 7 Pop Up Zone


Rose Date Papercess, ...

Scale Project No. 14005

1500 @A1, 5096@A3 Day, No. A-DA-740-010 14005 Drawn by North
AC_JF_CM
Rev

turner

Level 1,410 Crown Street Surry Hills MSCI 2010 Australia





LEGEND:



*** Proposed Building Envelope excludes Facade articulation & roof overhangs

CLIENT

CLIENT

CALIFORNIA DE LA PRODUCTION CONTROL PRESENCIONAL DE LA PRODUCTION DE LA PRO


Project Tile
SHEPHERDS BAY - STAGE 6 & 7
Nancamow Ave, Meadowbank NSW 2114 Australia


Envelope Comparison Diagrams
Stage 6 Pop Up Zone

Rest. Date Approved by Project No. 14005
State Project No. 14005
Day No. A-DA-740-030 14005 Drawn by North
AC_JF_CM
Rev

turner

Level 1, 410 Crown Street Surry Hills NSCJ 2010 Australia





*1. Typical Floor plate below Popup Levels 6 & 7 for 60 % Footprint Calculation

Total Stages 6 & 7


** 2. Stage 6 & 7 - Proposed Footprints combined to achieve 60% of floor plate below.


LEGEND


Approved Building Envelope

Proposed Building Footprint Zone

Proposed Building Footprint Zone Proposed Footprint for Popup - 50% of footprint of Typical Roor belo Approved Building Footprint Zone Approved Footprint Approved Building Footprint Zone
Approved Footprint of Typic









Stage 7 Proposed Popup Footprint for Levels 6 & 7

Stage 6 Proposed Popup Footprint for Levels 6 & 7

turner

Level 1, 410 Crown Street Surry Hills NSC/ 2010 Australia

D LCS Quality Environed Company BD 9++12++1, Licence Number 44+4 Nominated And Net (Noticine Tamer 44+5, ABN 44+44+44+11



Perspective View 4 Nancarrow Ave Main Site Link



Perspective View 2 Nancarrow Ave Stage 6 Entry



Perspective View 3 Nancarrow Ave Stage 6 Entry







Perspective View 3 Constitution Road Entry Building 7



Perspective View 3 Constitution Road Main Site Link




HORSE-MICH CONTROL AS THE SECRETARY REPORTED TO THE SECRETARY CONTROL AND CONT

Raporto
SHEPHERDS BAY-STAGE 6 & 7
Noncomov Ave, Meadowbank NSU 2114 Austalia
Cove, no
Perspectives
Perspective 03

S C3 Subj Probabil Corpo, CS Mr PAC | Installation - AC | Probabil - About 1986 Annual SM - B S No In-


3

SHEPHERDS BAY, MEADOWBANK CIVIL WORKS



LOCALITY PLAN DRAWING INDEX

DRG No.	DESCRIPTION	DRG No.	DESCRIPTION
C-0200	COVER SHEET	C-0260	STORMWATER LONGITUDINAL SECTIONS - SHEET 1
C-0201	NOTES SHEET	C-0261	STORMWATER LONGITUDINAL SECTIONS - SHEET 2
C-0202	KEY PLAN	C-0262	STORMWATER LONGITUDINAL SECTIONS - SHEET 3
C-0210	SITEWORKS PLAN - SHEET 1	C-0263	STORMWATER LONGITUDINAL SECTIONS - SHEET 4
C-0211	SIT BWORKS PLAN - SHEET 2	C-0264	STORMWATER PIT SCHEDULE
C-0212	SIT BWORKS PLAN - SHEET 3	C-0265	CATCHMENT PLAN
C-0213	SIT BWORKS PLAN - SHEET 4	C-0270	SIGNAGE AND LINEMARKING PLAN - SHEET 1
C-0214	SITEWORKS PLAN - SHEET 5	C-0271	SIGNAGE AND LINEMARKING PLAN - SHEET 2
C-0215	SIT BNORKS PLAN - SHEET 6	C-0272	SIGNAGE AND LINEMARKING PLAN - SHEET 3
C-0230	TYPICAL ROAD SECTIONS	C-0273	SIGNAGE AND LINEMARKING PLAN - SHEET 4
C-0240	CONSTITUTION ROAD LONGITUDINAL SECTIONS	C-0280	DETAILS SHEET 1
C-0245	CONSTITUTION ROAD CROSS SECTIONS - SHEET 1	C-0281	DETAILS SHEET 2
C-0246	CONSTITUTION ROAD CROSS SECTIONS - SHEET 2	C-0282	DETAILS SHEET 3
C-0247	CONSTITUTION ROAD CROSS SECTIONS - SHEET 3	C-0290	TURNING PATH PLAN - SHEET 1
C-0250	INTERSECTION PLAN CONSTITUTION ROAD/BOWDEN STREET	C-0291	TURNING PATH PLAN - SHEET 2



GENERAL NOTES

- TECHNICAL SPECIFICATIONS OR SPECIFIC INSTRUCTIONS ON DRAWINGS TAKE PRECEDENCE OVER THESE NOTES.
- DO NOT DEPART FROM THE DESIGN UNLESS AUTHORISED IN WRITING BY THE
- THESE DRAWINGS SHALL BE READ IN CONTINCTION WITH ALL ARCHITECTURAL THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH ALL ARCHITECTURAL AND OTHER CONSULTANTS: DRAWINGS AND SPECIFICATIONS AND WITH ANY OTHER WRITTEN INSTRUCTIONS AS MAY BE ISSUED DURING THE COURSE OF THE CONTRACT. ANY DISCREPANCY SHALL BE REFERRED TO THE INGINEER BEFORE PROCEEDING WITH THE WORK. CONSTRUCTION FROM THESE DRAWINGS, AND THEN ASSOCIATED CONSULTANTS: DRAWINGS IS NOT TO COMMENCE UNTIL APPROVED. BY THE RELEVANT AUTHORITIES.
- REFER TO ALL NOTES ON THESE DRAWINGS AND PREVIOUSLY MENTIONED DOCUMENTATION REFORE REGINNING CIVIL WORKS.
- ALL MATERIALS AND WORKMANSHIP SHALL REIN ACCORDANCE WITH THE ALL MATERIALS AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE RELEVANT AND CURRENT SPECIFIED STANDARDS AND WITH THE BY-LAWS AND ORDINANCES OF THE RELEVANT APPROVAL AUTHORITIES EXCEPT WHERE VARIED BY THE PROJECT SPECIFICATION AND/OR DRAWINGS.
- THE RELEVANT AUTHORITIES OCCUPATIONAL HEALTH AND SAFETY PRACTICES
- ALL DIMENSIONS AND LEVELS SHOWN ON THE DRAWINGS SHALL BE VERIFIED BY THE CONTRACTOR ON SITE. CIVIL DRAWINGS SHALL NOT BE SCALED FOR DIMENSIONS. REFER TO ARCHITECTURAL DRAWINGS FOR ALL DIMENSIONS AND THE ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCIES PRIOR TO
- UNLESS NOTED OTHERWISE, ALL DIMENSIONS ARE IN METRES (m) AND ALL LEVELS ARE IN METRES (m) TO AUSTRALIAN HEIGHT DATUM (AHD)
- GRADES TO PAVEMENTS TO BE AS IMPLIED BY RUS ON CIVIL GRADING PLAN. GRADES TO PAYEMENTS TO BE AS IMPLED BY ALS ON UNIX GRADING PLAN DRAWINGS. GRADE EVENLY BETWEEN NOMINATED RL'S. AREAS EXHIBITING PONDING GREATER THAN 5mm DEPTH WILL NOT BE ACCEPTED/ UNLESS IN A DESIGNATED SAG POINT.
- 10. IF THERE IS DOUBT REGARDING THE CIVIL DESIGN, CONTACT THE ENGINEER FOR CLARRICATION.
- 11. ALL ABBREVIATIONS ARE AS FOLLOWS:

EXISTING GROUND LEVEL FINISHED FLOOR LEVEL
REDUCED LEVEL
EASTING COORDINATE
NORTHING COORDINATE AUSTRALIAN HEIGHT DATUM UNLESS NOTED OTHERWISE UNPLASTICISED POLYVINYL CHLORIDE REINFORCED CONCRETE PIPE VITRIFIED CLAY PIPE FIBRE REINFORCED COMPOSITE FINSHED SURFACE LEVEL KERB AND GUTTER KERB ONLY NOMINAL FACE OF KERB TOP OF KERB BACK OF KERB DISH DRAIN MOUNTARIE KERR MOUNTABLE INTEGRAL KERB MOUNTABLE INTEGR INTEGRAL KERB INVERT LEVEL OBVERT LEVEL GRATED DRAIN TOP WATER LEVEL GALVANISED THICKENED EDGE FLUSHING POINT OMN PIPE PINC# RETAINING WALL ISOLATION JOINT
DOWELLED EXPANSION JOINT
SAWN JOINT KEYED JOINT TROWELED WEAKENED PLANE JOINT EXPANSION JOINT TOP OF WALL LEVEL ROTTOM OF WALL LEVE

BULK EARTHWORKS NOTES

MAP GRID OF AUSTRALIA

- 6.1. REFER TO GEOTECHNICAL INVESTIGATION REPORT FOR INFORMATION RELATING TO EXISTING GROUND CONDITIONS, GROUND WATER LEVELS, SITE TREATMENT AND
- 6.2. REFER TO 'EXISTING SERVICES AND FEATURES' NOTES BEFORE COMMENCING BULK EARTHWORKS.
- 6.3. TECHNICAL SPECIFICATIONS OR SPECIFIC INSTRUCTIONS CONTAINED IN THE GEOTECHNICAL REPORT TAKE PRECEDENCE OVER THESE NOTES.
- 6.4. ALL TOP SOIL, ORGANIC MATTER AND FILL MATERIAL SHALL BE REMOVED FROM ALL AREA SUNDER PROPOSED WORK LOCATIONS TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER. AREAS TO BE FULLY STRIPPED OF EXISTING FILL AND DARK BROWN BLACK UPPER ORGANIC ALLUVIUM.
- 6.5. CONTRACTOR SHALL PLACE SAFETY BARRIERS AROUND EXCAVATIONS IN ACCORDANCE WITH RELEVANT AUTHORITY SAFETY REGULATIONS
- 6.6. BULK EARTHWORKS DRAWINGS ARE NOT TO BE USED FOR DETAIL EXCAVATION.

SURVEY NOTES

- THE EXISTING SITE CONDITIONS SHOWN ON THE FOLLOWING DRAWINGS HAVE BEEN DERIVED FROM SURVEY INFORMATION SUPPLIED FROM H RAMSAY & COMPANY PTY LIMITED
- THE FOLLOWING SURVEY INFORMATION HAS BEEN TAKEN DIRECTLY FROM ORIGINAL SURVEY DOCUMENTS.

ORIGIN OF LEVELS SSM 1044 RL 2.55 (AHD)

- THE INFORMATION IS SHOWN TO PROVIDE A BASIS FOR DESIGN. BG&E PTY LTD DOES NOT GUARANTEE THE ACCURACY OR COMPLETENESS OF THE SURVEY BASE OR ITS SUITABILITY AS A BASIS FOR CONSTRUCTION DRAWINGS.
- SHOULD DISCREPANCIES BE ENCOUNTERED DURING CONSTRUCTION BETWEEN THE SURVEY DATA AND ACTUAL FIELD DATA, CONTACT BG&E PTY LTD.
- THE CONTRACTOR SHALL ARRANGE ALL SURVEY SETOUT TO BE CARRIED OUT
- BENCH MARK, SURVEY PEGS, LEVEL PEGS OR SUPPLEMENTARY REFERENCE MARKS SHALL NOT BE ADJUSTED OR MOVED WITHOUT WRITTEN APPROVAL FROM THE SUPERINTENDENT. THE CONTRACTOR SHALL TRANSFER ANY PEGS AFFECTED BY THE PROPOSED WORKS TO SIDE POSITIONS CLEAR OF OPERATIONS AND SHALL NOTE THE EXTENT OF THE MOVEMENT IN DISTANCE AND LEVEL

EXISTING SERVICES AND FEATURES NOTES

- THE CONTRACTOR MUST CONFIRM THE EXACT LOCATION AND EXTENT OF EXISTING SERVICES PRIOR TO CONSTRUCTION AND NOTIFY ANY CONFLICT WITH THE DRAWINGS IMMEDIATELY TO THE ENGINEER/SUPERINTENDENT.
- EXISTING SERVICES UNLESS SHOWN ON SURVEY PLAN HAVE BEEN PLOTTED FROM SERVICES SEARCH PLANS AND AS SUCH THEIR ACCURACY CANNOT BE GUARANTEED.
- IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO COMPLETE A 'DIAL BEFORE YOU DIG' SEARCH AND TO ESTABLISH THE LOCATION AND LEVEL OF ALL EXISTING SERVICES PRIOR TO THE COMMENCEMENT OF ANY WORK, ANY DISCREPANCIES SHALL BE REPORTED TO THE ENGINEER/SUPERINTENDENT.
 CLEARANCES SHALL BE OBTAINED FROM THE RELEVANT SERVICE AUTHORITY. SEARCH RESULTS ARE TO BE KEPT ON SITE AT ALL TIMES.
- THE CONTRACTOR HAS A DUTY OF CARE WHEN EXCAVATING NEAR SERVICES. DO NOT ASSUME DEPTHS OR ALIGNMENTS OF CABLES OR PLANT AS THESE MAY VARY SIGNIFICANTLY. THE CONTRACTOR MUST ACCEPT ALL RESPONSIBILITY TO DAMAGES TO EXISTING SERVICES AND SERVICE AUTHORITIES MAY SEEK COMPENSATION FOR DAMAGES CAUSED TO THEIR PROPERTY AND SUBSEQUENT
- THE CONTRACTOR SHALL ALLOW FOR THE CAPPING OFF, EXCAVATION AND REMOVAL OR RELOCATION (IF REQUIRED) TO RELEVANT AUTHORITES GUIDELINES OF ALL EXISTING SERVICES IN AREAS AFFECTED BY WORKS WITHIN THE CONTRACT AREA OR AS SHOWN ON THE DRAWINGS UNLESS DIRECTED OTHERWISE BY THE ENGINEER/SUPERINTENDENT.
- INTERRUPTION TO SUPPLY OF EXISTING SERVICES SHALL BE DONE SO AS NOT TO CAUSE ANY INCONVENIENCE TO SURROUNDING ALLOTMENTS, CONTRACTOR TO GAIN APPROVAL FROM THE RELEVANT AUTHORITIES FOR TIME OF INTERRUPTION.
- THE CONTRACTOR SHALL CONSTRUCT TEMPORARY SERVICES TO MAINTAIN THE CONTRACTOR SHALL CONSTRUCT TEMPORARY SERVICES TO MAINTAIN SUPPLY TO EXISTING BUILDINGS REMAINING IN OPERATION DURING WORKS TO THE SATISFACTION AND APPROVAL OF ANY RELEVANT AUTHORITIES. ONCE DIVERSION IS COMPLETE AND COMMISSIONED, THE CONTRACTOR SHALL REMOVE ALL SUCH TEMPORARY SERVICES AND MAKE GOOD TO THE SATISFACTION OF THE RELEVANT AUTHORITY/SUPERINTENDENT.
- EXISTING SERVICES, BUILDINGS, EXTERNAL STRUCTURES AND TREES SHOWN ON THESE DRAWINGS ARE EXISTING FEATURES PRIOR TO ANY DEMOLITION WORKS.
- ALL BRANCH GAS AND WATER SERVICES LINDER DRIVEWAYS BRICK PAVING AND CONSTRUCTION TRAFFIC MANEUVERING AREAS SHALL BE PROTECTED TO RELEVANT AUTHORITIES GUIDELINES.
- ALL EXISTING SERVICE UTILITIES COVERS AND GRATES ARE TO BE ADJUSTED (TO RELEVANT AUTHORITY GUIDELINES) TO SUIT NEW FINISHED SURFACE LEVELS WHERE APPLICABLE.
- IF EXISTING SERVICE UTILITY COVERS AND GRATES OR SURROUNDING SURFACE LEVELS ARE TO BE LOWERED, THE CONTRACTOR IS TO MAKE CERTAIN THAT MINIMUM COVERS (TO RELEVANT SERVICE AUTHORITY GUIDELINES) TO SERVICES ARE MAINTAINED. IF MINIMUM COVERS AREN'T MAINTAINED THE CONTRACTOR IS TO LOWER OR PROTECT SERVICES TO THE SATISFACTION OF THE RELEVANT SERVICE AUTHORITY/SUPERINTENDENT.

SUBSOIL DRAINAGE NOTES

- PROVIDE SUBSOIL DRAINS TO INTERCEPT GROUNDWATER SEEPAGE AND PREVENT WATER BUILD-UP BEHIND WALLS AND UNDER FLOORS AND PAVEMENTS. CONNECT SUBSOIL TO SURFACE DRAINS OR TO THE STORMWATER DRAINAGE SYSTEM AS APPLICABLE.
- ALL SUBSOIL PIPES SHALL BE 100mm SLOTTED CORRUGATED uPVC IN A FILTER SOCK U.N.O.
- FILTER SOCKS ARE TO BE POLYESTER PERMEABLE SOCKS CAPABLE OF RETAINING PARTICLES GREATER THAN 0.25mm IN SIZE. SECURELY FIT OR JOIN THE SOCK AT EACH JOINT.
- WHERE SUBSOIL DRAINS PASS UNDER EXTERNAL SLABS AND VEHICULAR PAVEMENTS, UNSLOTTED uPVC SEWER GRADE PIPE IS TO BE USED.
- SUBSOIL DRAINAGE TRENCHES ARE TO BE WRAPPED WITH PERMEABLE TEXTILE FABRIC 'BIDIM A12' OR EQUIVALENT.
- TO REDUCE GROUND WATER TRACKING WITHIN STORMWATER TRENCHES INSTALL A 3m LENGTH OF SUBSOIL PIPE IN PIPE TRENCHES DRAINING IN DIRECTION OF FALL OF PIPE AND CONNECT TO DOWNSTREAM STORMWATER DRAINAGE PIT.
- SUBSOIL MINIMUM CLEARANCE DEPTHS, MEASURED TO THE CROWN OF THE PPE, WHERE THE PIPE PASSES BELOW THE FOLLOWING ELEMENTS:

 1 DOORM BELOW FORMATION LEVEL OF THE PAVEMENT, KERS OR CHANNEL.

 AT THE AVERAGE GRADIENT OF THE BOTTOM OF FOOTINGS.
- AT JUNCTIONS OF SUBSOIL PIPES PROVIDE TEES, COUPLINGS OR ADAPTORS IN ACCORDANCE WITH AS2439.1.
- SURSOIL DRAINAGE TRENCHES SHALL RE A MINIMUM 300mm WIDE.
- GRADE THE TRENCH ELOOR EVENLY TO THE GRADIENT OF THE PIPELINE IF THE GRADE THE TREAM TOOK CEVENTY TO THE GRADUANT OF THE PREJUNC IT THE TRENCH FLOOR IS ROCK, CORRECT ANY IRREGULARITIES WITH COMPACTED BEDDING MATERIAL. BED PIPING ON A CONTINUOUS UNDERLAY OF BEDDING MATERIAL, AT LEAST 75mm THICK AFTER COMPACTION, LAY THE PIPE WITH ONE LINE OF PERFORATIONS AT THE BOTTOM.
- PLACE THE MATERIAL IN THE PIPE SURROUND IN LAYERS SMALLER THAN OR EQUAL TO 200mm LOOSE THICKNESS, AND COMPACT WITHOUT DAMAGING OR DISPLACING PIPING.

SUBGRADE COMPACTION NOTES

- 1. THE EXPOSED SURGRADE (I.E. THE LOWER COURSE OF PAVEMENT RELOW THE THE EXPOSED SUBGRADE (I.E. THE LOWER COURSE OF PAYEMENT BELOW THE SUB-BASE) AFTER STRIPPING AND/OR EXCAVATION SHALL BE PROOF ROLLED USING MOT FEWER THAN 5 PASSES WITH A 10 TONNE DEAD WEIGHT STEEL SMOOTH-DRUM ROLLER UNDER THE SUPERVISION OF AN EXPERIENCED GEOTECHNICAL ENGINEER, ANY AREAS EXHBITING EXCESSIVE DEFLECTION/MOVEMENT UNDER ROLLER SHALL BE REMOVED TO THE SATISFACTION OF THE GEOTECHNICAL ENGINEER TO A MINIMUM DEPTH OF SOORM AND THEN DESCRIPTION OF THE GEOTECHNICAL ENGINEER TO A MINIMUM DEPTH OF SOORM AND THEN BACKFILLED WITH APPROVED ENGINEERED FILL TO MEET THE DESIGN SUBGRADE
- 2. ENGINEERED FILL TO TO BE PLACED IN LAYERS NOT EXCEEDING 250mm LOOSE PROBLEMS AND COMPACTED TO 98% OF STANDARD MAXIMUM DRY DENSITY
 (SMDD) AND TO WITHIN 2% OF STANDARD OPTIMUM MOISTURE CONTENT (SOMD) IN ACCORDANCE WITH AS 1289 5.11. APPROVED BACKFLL MATERIAL MAY BE
 CRUSHED ROCK OR SANDY LOAM WITH A PLASTICITY INDEX LESS THAN 15%.
- 3. TESTING OF THE SUBGRADE SHALL BE CARRIED OUT BY AN APPROVED N.A.T.A REGISTERED LABORATORY.
- 4. ALL FILL MATERIAL SHALL BE FROM A SOURCE APPROVED BY THE SUPERINTENDENT AND SHALL COMPLY WITH THE FOLLOWING.

 FREE FROM ORGANIC AND PERISHABLE MATTER

 MAXIMUM PARTICLE SIZE = 75mm

 MAXIMUM PLASTICITY INDEX = 15%

SUB-BASE COURSE COMPACTION NOTES

- 1. PAVEMENT "SUB-BASE" (I.E THE INTERMEDIATE OR LOWER COURSE OF THE PAYEMENT BELOW THE BASE) SHALL BE CONSTRUCTED FROM MATERIAL AS SPECIFIED ON DRAWINGS AND COMPACTED TO 98% OF THE STANDARD MAXIMUM DRY DENSITY (SMDD) AND WITHIN 2% OF STANDARD OPTIMUM MOISTURE CONTENT
- BE FREE OF CLAY LUMPS, ORGANIC MATTER AND OBJECTIONABLE QUANTITIES OF DELETERIOUS SUBSTANCES.
- 3. ALL MATERIAL REQUIREMENTS APPLY BOTH PRIOR TO AND AFTER PLACEMENT OF

BASE COURSE COMPACTION NOTES

- 1. PAVEMENT "BASE" (I.E THE HIGHEST COURSE OF THE PAVEMENT BELOW THE SURFACING SHALL BE CONSTRUCTED FROM MATERIAL AS SPECIFIED ON DRAWINGS AND COMPACTED TO 98% OF THE STANDARD MAXIMUM DRY DENSITY (SMDD) AND WITHIN 2% OF STANDARD OPTIMUM MOISTURE CONTENT (SOMC) IN ACCORDANCE WITH AS 1289 5.1.1 (EXCEPT CONCRETE PAVEMENT, WHERE THE CONCRETE IS THE
- ALL BASE MATERIAL SHALL BE HARD, DURABLE AND THE MATERIALS SHALL BE FREE OF CLAY LUMPS, ORGANIC MATTER AND OBJECTIONABLE QUANTITIES OF DELETERIOUS SUBSTANCES.
- ALL MATERIAL REQUIREMENTS APPLY BOTH PRIOR TO AND AFTER PLACEMENT OF THE PAVEMENT

GENERAL PAVEMENT NOTES

- TECHNICAL SPECIFICATIONS CONTAINED WITHIN THE GEOTECHNICAL REPORT TAKE PRECEDENCE OVER THESE NOTES.
- PRIOR TO DELIVERY OF ANY MATERIAL TO THE SITE, THE SOURCE OF ALL MATERIALS AND ANY RELEVANT CERTIFICATES STATING THAT THE MATERIAL SATISFIES THE SPECIFIED REQUIREMENTS SHALL BE PROVIDED TO THE SUPERINTENDENT FOR APPROVAL
- TESTING OF PAVEMENT MATERIALS WILL NORMALLY BE PERFORMED ON SAMPLES
 TAKEN AT THE SOURCE SITE PRIOR TO DELIVERY TO THE SITE AND IN THEIR
 FINAL CONDITIONS AFTER PLACEMENT AND COMPACTION. HOWEVER, THE
 PROPERTIES SPECIFIED AND FINAL ACCEPTANCE ARE APPLICABLE TO THE
 MATERIALS IN THEIR FINAL CONDITION IN THE PAVEMENT.
- 4. FINAL ACCEPTANCE WILL BE CONDITIONAL ON NO SIGNIFICANT CHANGE IN PROPERTIES DUE TO SEGREGATION OR CONTAMINATION DURING SUBSECUENT PAVEMENT WORKS.

STORMWATER DRAINAGE NOTES

- THE STORMWATER DESIGN SHOWN ON THESE DRAWINGS HAS BEEN CARRIED OUT IN ACCORDANCE WITH CITY OF RYDE COUNCIL'S REQUIREMENTS, AUSTRALIAN RAINFALL AND RUNOFF (AR&R) GUIDELINES AND RELEVANT AUTHORITIES
- FINISHED SURFACE LEVELS SHOWN ON CIVIL GRADING PLAN DRAWINGS TAKE
- ALL STORMWATER WORK IS TO COMPLY WITH AS3500 PART 3.
- PROTECTION OF PIPES EXPOSED TO LOADS EXCEEDING THE W7 WHEEL LOAD OF 70kN SHALL BE THE CONTRACTOR'S RESPONSIBILITY.
- 5. NO CONSTRUCTION LOADS SHALL BE APPLIED TO uPVC PIPES.
- EXISTING STORMWATER PIPE LOCATIONS AND INVERT LEVELS TO BE CONFIRMED PRIOR TO COMMENCEMENT OF CONSTRUCTION
- FOR ALL STORMMATER DRAINAGE PITS REFER TO TYPICAL PIT CHAMBER DETAILS ON THESE DRAWINGS. IF PIT LID SIZE IS SMALLER THAN THE PIT CHAMBER SIZE THEN THE PIT LID IS TO BE CONSTRUCTED ON THE CORNER OF THE PIT CHAMBER WITH THE STEP IRONS DIRECTLY BELOW, ALTERNATIVELY THE PIT LID TO BE USED, IS TO BE THE SAME SIZE AS THE PIT CHAMBER.
- GALVANIZED STEP IRONS SHALL BE PROVIDED AT 300 CTRS FOR PITS HAVING A
- PIPES 300 DIA. AND LARGER TO BE REINFORCED CONCRETE PIPES (RCP) CLASS '4' APPROVED SPIGOT AND SOCKET WITH RUBBER RING JOINTS U.N.O.
- 10. PIPES UP TO 300 DIA, SHALL BE SEWER GRADE uPVC WITH SOLVENT WELDED
- EQUIVALENT STRENGTH VCP OR FRC PIPES MAY BE USED IF RELEVANT APPROVAL AUTHORITY AND SUPERINTENDENT PERMITS.
- BEDDING TYPE SHALL BE TYPE HS2 FOR RCP CONFORMING TO AS4058. WHERE NECESSARY THE OVERLAY ZONE SHALL BE REDUCED TO ACCOMMODATE PAVEMENT REQUIREMENTS.
- PIPES SHALL BE LAID ON A 75mm THICK SAND BED. IN ALL CASES BACKFILL TRENCH WITH SAND TO 200mm ABOVE THE PIPE. WHERE PIPE IS UNDER PAVEMENTS BACKFILL REMAINDER OF TRENCH TO UNDERSIDE OF PAVEMENT WITH SAND OR APPROVED GRANULAR MATERIAL COMPACTED IN 150mm LAYERS TO 98% STANDARD MAXIMUM DRY DENSITY IN ACCORDANCE WITH AS 1289 5.2.1 (OR A DENSITY INDEX OF NOT LESS THAN 75).
- WHERE TRENCHES ARE IN ROCK THE PIPE SHALL BE BEDDED ON A MINIMUM OF 50mm CONCRETE BED (OR 75mm BED OF 12mm BLUE METAL) UNDER THE BARREL OF THE PIPE.
- ENLARGERS, CONNECTORS AND JUNCTIONS TO BE PREFABRICATED FITTINGS WHERE PIPES ARE LESS THAN 300 DIA.
- CARE IS TO BE TAKEN WITH LEVELS OF STORMWATER LINES, GRADES SHOWN ARE NOT TO BE REDUCED WITHOUT PRIOR WRITTEN APPROVAL FROM THE
- GRATES AND COVERS SHALL CONFORM TO AS3996 AND AS1428.1 AT ALL TIMES DURING CONSTRUCTION OF THE STORMWATER PITS.
- ALL EXISTING STORMWATER DRAINAGE LINES AND PITS THAT ARE TO REMAIN ARE TO BE INSPECTED AND CLEANED, DURING THIS PROCESS ANY PART OF THE STORMWATER DRAINAGE SYSTEM THAT WARRANTS REPAIR SHALL BE REPORTED TO THE SUPERINTENDENT AND ENGINEER FOR FURTHER DIRECTIONS.

KERBING NOTES

INCLUDES ALL KERBS, GUTTERS, DISH DRAINS, CROSSINGS AND EDGES.

- ALL KERBS, GUTTERS, DISH DRAINS AND CROSSINGS TO BE CONSTRUCTED ON MINIMUM 75mm GRANULAR BASE COURSE MATERIAL COMPACTED TO A MINIMUM 98% MODIFIED MAXIMUM DRY DENSITY IN ACCORDANCE WITH AS 1289 5.2.1.
- EXPANSION JOINTS (E.J) TO BE FORMED FROM 10MM COMPRESSIBLE CORK FILLER BOARD FOR THE FULL DEPTH OF THE SECTION AND CUT TO PROFILE. EXPANSION JOINTS TO BE LOCATED AT DRAINAGE PITS, ON TANGENT POINTS OF CURVES AND ELSEWHERE AT 12M CENTRES EXCEPT FOR INTEGRAL KERS WHERE THE EXPANSION JOINTS ARE TO MATCH THE JOINT LOCATIONS IN SLABS.
- WEAKENED PLANE JOINTS (WPJ) ARE TO BE LOCATED AT A MAX 1.5 x WIDTH OF THE PAYEMENT. WEAKENED PLANE JOINTS (WPJ) ARE TO BE A MINIMUM 3mm WIDE WITH A JOINT DEPTH TO BE A MINIMUM OF 1/4 THE TOTAL DEPTH OF THE SECTION.
- 4. ALL KERBING OR DISH DRAINS TO BE STEEL FLOAT FINISHED.
- WHEN CONSTRUCTING NEW KERB TO EXISTING AND IN THE REPLACEMENT OF KERBS, EXISTING ROAD PAYEMENT IS TO BE SAMPCUT 900mm FROM LIP OF GUTTER. UPON COMPLETION OF NEW KERBS, NEW BASE COURSE AND SURFACE IS TO BE LAID 900mm WIDE TO MATCH EXISTING MATERIALS AND THICKNESS.
- EXISTING ALLOTMENT DRAINAGE PIPES ARE TO BE BUILT INTO THE NEW KERB WITH A 125 \times 75 GALVANISED RHS.
- EXISTING KERBS ARE TO BE COMPLETELY REMOVED WHERE NEW KERBS ARE

SSUED FOR INFORMATIO A 23.12.14 ISSUEU FOR EV DATE DESCRIPTION REVISIONS

HOLDMARK

2/2-4 GIFFNOCK AVENUE, MAQQUARIE PARK NSW 2113

Sydney Office L2 8 Windmill St. Sydney NSW 2000 P/+61 2 9770 3300 E/info∰bgreng.com bgeeng.com-




SHEPHERDS BAY MEADOWBANK


PRELIMINARY ONLY DESIGNED APPROVED TB NK AT A1 SI

NOTES SHEET


\$10076 C-0201 Α


155 STD STOORS TOO DRAWNOOZ CIVIL VIUTOCAD STOORS DRG-C-0201 DWG







DESC Day Limite









PROFILE _ CONSTITUTION ROAD (MC10)

A	23.12.14	ISSUED FOR INFORMATION	
REV	DATE	DESCRIPTION	RVD

HOLDMARK

2/2-4 GIFFNOOK AVENUE, MAQQUARIE PARK NSW 2113

Sydney Office— L2 8 Windmill St Sydney NSW 2000 P/+61 2 9770 3300 E/info@bgeeng.com

SHEPHERDS BAY MEADOWBANK


PRELIMINARY ONLY
NOT TO BE USED FOR CONSTRUCTION


TB NK 1:250H, 1:50V

CONSTITUTION ROAD LONGITUDINAL SECTIONS


S14053 C-0240


5: 986 SYD/S10016/100 DRAW/100,2 CIVIL VAUTOCAD/S10016-DRG-C-0240,DWG 28/2/2014 10:4921 AM







CHAINAGE 75









A 2312.14 ISSUED FOR INFORMATION
REV DATE DESCRIPTION
REVISIONS HOLDMARK 2/2-4 GIFFNOCK AVENUE, MAQQUARIE PARK NSW 2113 Sydney Office— L2 8 Windmill St Sydney NSW 2000 P/+61 2 9770 3300 E/info@bgeeng.com SHEPHERDS BAY MEADOWBANK PRELIMINARY ONLY TB NK CONSTITUTION ROAD

CROSS SECTIONS


SHEET 1 S140<u>53</u>


NOTE
* - RETAINING WALL BY OTHERS

P.166F.SYD \S100 (B\100 DRAW\100.2 CIVIL \WITTOCAD\S100(16-DR6-C-0245.DW6 2372/2014 1048/31 AM


Α

C-0245







CHAINAGE 210



CHAINAGE 195



CHAINAGE 180



CHAINAGE 165

1		
A 2	23.12.14 ISSUED FOR INF	RMATION
REV I	DATE DESCRIPTION	
	R	EVISIONS
HOL	_DMARK	EVISIONS

Sydney Office— L2 8 Windmill St Sydney NSW 2000 P/+61 2 9770 3300 E/info@bgeeng.com

SHEPHERDS BAY MEADOWBANK


STATUS		IMINAF 0 BE USED FOR	RY ONLY
DRAWN TB	DESIGNED NK	CHECKED	APPROVED
DATUM	GRID	SCALE	
AHD		1:100	AT A1


CONSTITUTION ROAD CROSS SECTIONS


SHEET 3 S14053 C-0247

© BG&E Pty Limited

P. SEE: SYD STID IS VIO DRAWNIO.2 CIVIL VAUTOCAD STODIS-DRG-C-024 I DWG 27/2/2014 (04945) AM







A 23.12.14 ISSUED FOR INFORMATION REV DATE DESCRIPTION

HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office— L2 8 Windmill St Sydney NSW 2000 P/+61 2 9770 3300 E/info€bgeeng.com


SHEPHERDS BAY MEADOWBANK

STATUS	PRELIMINARY ONLY NOT TO BE USED FOR CONSTRUCTION				
DRAWN TB	DESIGNED NK	C HECKE D	APPROVED		
DATUN	580	SCALE 4 40011	. 1207		

STORMWATER LONGITUDINAL SECTIONS SHEET 2

S10076 C-0261

P. NEBELSYON SHITZANTH DRAWSHILZ COMENAUTOCAUSSHITZA-DRE-C-TZANDW 5 23/27/215-16-6-27-AH



A 23.12.14 ISSUED FOR INFORMATION REV DATE DESCRIPTION REVISIONS

HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office— L2 8 Windmill St Sydney NSW 2000 P/+61 2 9770 3300 E/info@bgeeng.com


SHEPHERDS BAY MEADOWBANK

PRELIMINARY ONLY YN DESIGNED NK 1:100H, 1:20V

STORMWATER LONGITUDINAL SECTIONS SHEET 3

S10076 C-0262

Α





HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—

L2 8 Windmill St Sydney NSW 2000 P/+61 2 9770 3300 E/info@bgeeng.com

SHEPHERDS BAY MEADOWBANK


STATUS		IMINAR O BE USED FOR	Y ONL	Υ
DRAWN TB	DESIGNED NK	C HECKE 0	APPROVED	
DATUN	680	SCALE		
AHD	MGA	1:100H	l, 1:20V	AT A1

STORMWATER LONGITUDINAL SECTIONS SHEET 4

S10076 C-0263

L PASSENSYDASTITAN TIL DRAWN TILZ CIVIL NABTOCABASTITAL DRS-C-1212 BWS 83/12/21% TILA NATARAS

Α




PIT / NODE DETAILS				Version 8			
Name	Max HGL	Max Pond	Max Surface	Max Pond	Min	Overflow	Constraint
LOCAMIC I CAR		HGL	Flow Arriving	Volume	Freeboard	(cu.m/s)	
			(cu.m/s)	(cu.m)	(m)		
NA.1	7.7900	9.0300	11.4550	0.6000	0.4100	0.0000	Inlet Capacity
NA.2	6.8600		0.0090		2.2000	0.0000	
NA.3	6.2700	9.0400	0.0920	5.3000	2.6200	0.0000	Inlet Capacity
NA.4	4.7800		0.0000		1.8700	0.0000	None
NA.5	4.2800	5.0700	0.2400	1.7000	0.6900	0.1420	Inlet Capacity
NA.6	3.9100	5.1800	0.1710	2.1000	1.1300		Inlet Capacity
NA.7	3.6800		0.0000		1.8200	0.0000	
NA.8	3.2500		0.0000		1.9000	0.0000	
NA.9	2.8500		0.0000		2.3000	0.0000	1000
NA.10	2.4200		0.0000		1.1800	0.0000	None
NA.11	2.0100		0.0000		1.9000	0.0000	None
NA.12	1.3700		0.0000		1.6200		None
NA.13	0.4700		0.0000				
OA.1	13.8700		0.3680		0.9700	0.1800	Inlet Capacity
OA.2	12.8100		0.2560		1.0000	0.0960	Inlet Capacity
OA.3	8.9200		0.1230		1.0300	0.0400	Inlet Capacity
OB.1	9.3100		0.0200		1.3300	0.0000	None
OB.2	9.1400		0.0500		1.3500	0.0100	Inlet Capacity
OB.3	7.7900		0.0330		1.3300	0.0000	None
OC.1	7.9100		0.0130		1.3500	0.0000	None
QA.1	6.3300	7.9300	0.0080	0.1000	1.5800	0.0000	Inlet Capacity
QA.2	5.3400	6.9000	0.0100	0.1000	1.5500	0.0000	Inlet Capacity
QA.3	3.9400		0.0170		1.4000	0.0040	Inlet Capacity
QB.1	5.9500	7.5000	0.0180	0.2000	1.5200	0.0000	Inlet Capacity
QB.2	4.8800	6.4800	0.3080	0.9000	1.4900	0.2130	Inlet Capacity
QB.3	4.7000	5.2700	0.2350	0.9000	0.4800	0.1370	Inlet Capacity
QE.1	5.8000		0.1630		0.5900	0.0830	Inlet Capacity
QC.3	5.7200		0.0260		0.5500	0.0000	None
RA.1	4.8000	5.1800	0.6780	21.5000	0.1000	0.0000	Inlet Capacity
RB.1	2.7800	4.0200	0.1030	0.4000	1.1600	0.0000	Inlet Capacity
RC.1	3.8000		0.0740		1.1800	0.0000	None
QF.1	8.4400		0.0440		1.5000	0.0000	None
QD.1	8.4100	9.8500	0.2370	0.9000	1.3500		Inlet Capacity
QC.2	8.1400		0.0190		1.0400	0.0040	Inlet Capacity


Name	Max	Paved	Grassed	Paved	Grassed	Supp.	Due to Storm
	Flow Q	Max Q	Max Q	Tc	Tc	Tc	
	(cu.m/s)	(cu.m/s)	(cu.m/s)	(min)	(min)	(min)	
C NA.2	0.0090	0.0080	0.0010	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C NA.3	0.0580	0.0540	0.0040	5.2400	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C NA.5	0.0250	0.0230	0.0020	5.2900	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C NA.6	0.0360	0.0340	0.0030	5.2300	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OA.1	0.3680	0.3430	0.0260	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OA.2	0.0760	0.0710	0.0050	5.0900	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OA.3	0.0290	0.0270	0.0020	5.2100	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OB.1	0.0200	0.0190	0.0010	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OB.2	0.0500	0.0470	0.0030	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OB.3	0.0240	0.0220	0.0020	5.2100	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C OC.1	0.0130	0.0120	0.0010	5.2100	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QA.1	0.0080	0.0080	0.0010	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QA.2	0.0100	0.0090	0.0010	5.1000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QA.3	0.0170	0.0160	0.0010	5.1900	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QB.1	0.0180	0.0170	0.0010	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QB.2	0.3080	0.2860	0.0220	5.1000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QB.3	0.0220	0.0200	0.0020	5.3300	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C QE.1	0.0210	0.0190	0.0010	5.2000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QC.3	0.0220	0.0210	0.0020	5.2000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C RA.1	0.6780	0.5420	0.1360	5.0000	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C RB.1	0.1030	0.0820	0.0210	5.3500	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C RC.1	0.0740	0.0590	0.0150	5.0000	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C QF.1	0.0440	0.0410	0.0030	5.0000	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C QD.1	0.2370	0.2160	0.0210	10.0000	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C QC.2	0.0090	0.0090	0.0010	5.0900	10.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
C PA.1	0.4480	0.3480	0.1000	10.0000	10.0000	0.0000	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
C PB.1	0.0290	0.0080	0.0210	5.0000	5.0000	0.0000	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1


PIPE DETA	AILS				
Name	Max Q	Max V	Max U/S	Max D/S	Due to Storm
	(cu.m/s)	(m/s)	HGL (m)	HGL (m)	
P NA.1	13.9080	4.4700	6.9690	6.8600	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.2	13.9140	4.2800	6.5950	6.2740	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.3	14.2580	7.6900	5.4530	4.7760	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.4	14.3430	7.1900	4.3890	4.2830	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.5	14.8650	3.2900	3.9530	3.9060	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.6	15.1660	3.3500	3.7340	3.6790	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.7	15.1780	3.3600	3.5730	3.2530	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.8	15.1740	3.3500	3.1800	2.8460	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.9	15.5160	3.4300	2.7930	2.4200	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.10	15.5800	3.5500	2.0590	2.0100	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.11	15.6020	4.0600	1.5040	1.3740	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P NA.12	15.5920	5.0400	0.6070	0.4670	AR&R 100 year, 2 hours storm, average 53.0 mm/h, Zone 1
P OA.1	0.2050	3.9500	13.5450	12.8120	AR&R 100 year, 15 minutes storm, average 154 mm/h, Zone 1
P OA.2	0.3320	6.1100	12.3430	8.9180	AR&R 100 year, 15 minutes storm, average 154 mm/h, Zone 1
P OA.3	0.4030	4.3000	8.7820	7.6180	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P OB.1	0.0200	1.4300	9.2630	9.1440	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P OB.2	0.0610	2.9400	9.0360	7.7950	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P OB.3	0.1040	2.2800	7.7350	7.5400	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1


Name	Max Q	Max V	Max U/S	Max D/S	Due to Storm
	(cu.m/s)	(m/s)	HGL (m)	HGL (m)	
P OC.1	0.0130	1.2300	7.8700	7.7950	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QA.1	0.0080	1.8100	6.2960	5.3360	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QA.2	0.0180	2.1800	5.2810	3.9370	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QA.3	0.0310	0.3900	3.9350	3.9060	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P QB.1	0.0180	2.3500	5.8910	4.8850	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QB.2	0.1130	3.4500	4.7160	4.6960	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QB.3	0.2080	1.8800	4.4080	4.2830	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P QE.1	0.0780	0.7000	5.7480	5.7230	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P QC.3	0.3320	4.4000	4.7970	3.9060	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P RA.1	0.6570	3.0900	4.2850	3.5640	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P RB.1	0.1020	2.0100	2.6530	2.6090	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P RC.1	0.1600	7.3200	3.5610	2.0100	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P QF.1	0.0440	0.6900	8.4070	8.4050	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QD.1	0.1390	3.9400	8.2140	8.1360	AR&R 100 year, 1.5 hours storm, average 62.0 mm/h, Zone 1
P QC.2	0.2330	5.2500	7.6810	5.7230	AR&R 100 year, 15 minutes storm, average 154 mm/h, Zone 1
P PA.1	0.1300	1.6300	5.4890	4.7760	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1
P PB.1	0.3390	2.1300	5.1080	4.2830	AR&R 100 year, 25 minutes storm, average 122 mm/h, Zone 1














PLAN - KERB RAMP










BLEND TO EXISTING PAVEMENT DETAIL


P-186E 15/10/15/10076/1007 DRAWN100.2 CIVIL VAUTOCAD 15/10078-DRG-C-028/10/WG 23/12/2014 10:51-16 AM















EDGE STRIP (ES)



SECTION THROUGH MOUNTABLE ISLAND SCALE 1:20

		1	
A	23.72.14	ISSUED FOR INFORMATION	
REV	DATE	DESCRIPTION	R
		REVISIONS	
		REVISIONS	

Sydney Office-L2 8 Windmill St Sydney NSW P/+61 2 9770 3300 E/info∰bgeeng.com


SHEPHERDS BAY MEADOWBANK


PRELIMINARY ONLY
NOT TO BE USED FOR CONSTRUCTION TB NK MGA 1:10 1:20

"DETAILS SHEET 1


^{ECT №} S10076 REW. A BG&E Pty Limited C-0280











SECTION B

A 23.12.14 ISSUED FOR INFORMATION
REV DATE DESCRIPTION REVISIONS HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office— L2 8 Windmill St Sydney NSW 2000 P/+61 2 9770 3300 E/info€bgeeng.com

SHEPHERDS BAY MEADOWBANK


PRELIMINARY ONLY MGA 1:10 1:20


DETAILS SHEET 2


S10076 C-0281


PASSENSYON SHEWN HE DRAWN HER COMENSUITOCADAS HEWA-DRE-C-1281 DWE-SYNZYEN HANSEN AN















GRATED PIT WITH RAISED STEEL GRATE DETAIL
SCALE: 120



_			
Α	23.12.14	ISSUED FOR INFORMATION	
REV	DATE	DESCRIPTION	RV

HOLDMARK

2/2-4 GIFFNOCK AVENUE, MACQUARIE PARK NSW 2113

Sydney Office—
L2 8 Windmill St Sydney NSW 200
P/-61 2 9770 3300
E/info@bgeong.com

0 3300 eng.com

SHEPHERDS BAY MEADOWBANK


PRELIMINARY ONLY NOT TO BE USED FOR CONSTRUCTION					
DRAWN TB	DESIGNED NK	CHECKED	APPROVED		
DATUM AHD	GRID MGA	1:10 1:20			A1 sız


DETAILS SHEET 3

S10076 | DRAWING No. C-0282 | REV

A BOXE Pty Lincitro

PAGE S YD S1006 (00 DRAWN) 00.2 CIVIL VAUTOCAD S10016-DRG-C-0282DWG 23/2/2014 1051:86 PW







MEADOWBANK, SHEPHERDS BAY Stages 6-7

detailed landscape + public domain plan

Development Assessment Submission Project Ref: HOL07

> 19 December 2014 Issue [C]



2 place design group.

		Date	lssu∈
Meadowbank Stages 6-7 Detailed Landscape + Public Domain Plan	Development Assessment Submission	17.12.2014	A
Meadowbank Stages 6-7 Detailed Landscape + Public Domain Plan	Development Assessment Submission	18.12.2014	В
Meadowbank Stages 6-7 Detailed Landscape + Public Domain Plan	Development Assessment Submission	18.12.2014	C

Contents

Introduction	4
Development Control Conditions	5
Pedestrian and Cycleway Plan (development wide)	6
Street Tree Strategy (developemnt-wide)	7
DESIGN: THE MASTERPLAN	
Landscape Design Intend Statement + Design Drivers	8
Combined 6-9 Masterplan	9
6-7 Masterplan	10
Central Spine / Tree Top Walk	1 1
Building 6 Private Common Area (Courtyard)	13
Site Links Ease + West	14
Nancarrow Road	16
Constiution Road Frontage	17
STRATEGY: SITE AND ELEMENTS	
Tree + Softscape Strategy	18
Indicative Planting Stragety + Schedule	19
Streetscape Strategy	20
Tree Retention / Removal Strategy	21
Landscape Materiality	22
Materails Strategy Diagram	23
Lighting Strategy Diagram	24
Furniture Strategy Diagram	25
Rooftop Garden Strategy	26
APPENDICIES	
A Parformance Consideration	

A Performance Specification

B Detailed Landscape Grading Plan

INTRODUCTION

"The project represents an opportunity to bring about positive change in current residential design trends by celebrating and bringing to life both the natural landscape and rich cultural history of the site in the landscape of the new development"

This document outlines the proposed Landscape Design Concept (DA) that fulfils the conditions of and guidelines set in the Major Project.

Concept Plan Application for the Shepherds Bay residential development.

The project represents an opportunity to bring about positive change in current residential design trends by celebrating and bringing to life both the natural landscape and rich cultural history of the site in the landscape of the new development. It will also ensure that the Shepherds Bay site Landscape Design meets both the Proponents vision for the site and Council's planning objectives, long term objectives and area specific Public Domain Manual,

The landscape design provides solutions that reflect the image and character of the Shepherds Bay Site as a fully integrated residential / parkland environment reflecting both the history and culture of the site.

Water usage, recycling and movement are a key part of this history and will be reflected throughout the landscape design. The landscape design will draw upon a rich and varied site history:- the aim to enhance and create a culturally significant landscape setting that transcends past and present. In this way the landscape will serve to educate visitors and residents whilst enhancing the sense of place and creating a unique identity for Shepherds Bay.

The enjoyable and safe interaction between visitor, resident and the Water Sensitive Urban Design initiatives used through out the development will be a key area of focus in the landscape. The retention of significant existing vegetation where possible will be combined with an innovative site wide planting strategy. Structured planting using a combined native and exotic plant palette is proposed.

The creation of view corridors to the river precinct is seen as an integral component to the landscape and urban design philosophy. There will be an increase in biodiveristy through street trees, integrated WSUD and planting to both public and private areas The landscape design philosophy recognises the current trends in the new home owners demographic. It is accepted that there will be a strong trend of responding to an increased community expectation of a range of active and passive recreational uses. Pedestrian and cycle movement will also be addressed to the wider landscape and surrounding communities including legible connections and cycle locking facilities. This will be in accordance with the control documents and approvals to date.

A vibrant central 3000m2 contiguous open space plaza at the core of the development on the waterfront will be for passive & active recreation multi-use and adaptable for residents and public use. It is intended that this space become a place of celebration for community events, meeting people and taking advantage of the river views. A cafe integrated into the built form at this location will ensure activation so the development reaches capacity.

A Holistic approach to the landscape design combined with the careful interaction of landscape & architectural elements across the site will result in a 'big picture' design creating and reinforcing the local identity, character and sense of place.

A sensitive and appropriate standard of landscape design is to be applied to the Shepherds Bay development so that the practical, aesthetic and social needs of the residents and community are realised. Detailed design of all public domain areas are to be based on the CPTED principles for safety and security. The concept plan designs are indicative and intended as a guide to future detailed designs.



Wider Context Plan NTS



Meadowbank, Shepherds Bay Site and Stage Context Plan NTS

DEVELOPMENT CONTROL CONDITIONS

LANDSCAPE / PUBLIC DOMAIN RELATED

The following development control conditions have been applied to the landscape design.

1(c). Provide a public domain plan which illustrates the proposed public domain treatment including streets and setback areas, landscaping, lighting and public and communal open spaces and which is in accordance with Ryde City Council's Public Domain Technical Manual

B1(e). Provide an integrated water sensitive urban design (WSUD) strategy for the entire site.

B1(f). Include a pedestrian and cycleways plan that demonstrates that the proposed routes are both viable and integrated with Council's plans for the surrounding

11. Landscaping: Future DAs shall include detailed landscape plans for public and private open space areas, street setbacks areas and for the landscape treatment of all adjoining public domain areas and road reserves in accordance with the approved Public Domain Plan.

12. Public Domain: Future DAs shall provide the detailed design for the upgrade of all road reserves adjacent to the development to the centre line of the carriageway, including landscaping, street trees, accessible pedestrian pathways, street lighting, cycle ways on Constitution Road and Nancarrow Avenue, and any other necessary infrastructure in accordance with the approved Public Domain Plan. Where the detailed design necessitates an increase in the width of the road reserve, building setbacks are to be increased to retain the approved setback to the road reserve alignment. The road reserve works are to be completed by the proponent prior to occupation of each stage.

15. Open Space/Public Access: Future DAs shall include detailed landscape plans for the embellishment of publicly accessible open space areas. These areas shall include high quality landscaping and paved areas and a variety of recreation facilities which may include BBOs, seating, water features, grassed areas, paths, shade trees, bicycle racks and exercise equipment/games.

16. Open Space/Public Access: Future DAs shall include detailed landscape plans which demonstrate accessible paths of travel for all persons for at least two of the northsouth routes between Constitution Road and the Foreshore with one of the routes including the Lower Riparian linear park and a second path either along the Central Spine or the public pathway associated with Stage One.

Landscape plans will also include the detailed design of at least 1 north-south cycle path linking Constitution Road through the site to the existing foreshore cycleway.

17. Open Space/Public Access: Future DAs shall clearly set an appropriate legal mechanism for creating rights of public access to all publicly accessible areas of open space, drainage reserves and through site links, with the relevant instrument/s to be executed prior to the issue of the occupation certificate.

9.6. New Pedestrian Spine 2 (North) Publicly Accessible Open Space (Development Stage 6): This new publicly accessible open space will be delivered as part of Indicative Development Stage 6.

This through site and pedestrian connection is intended to be simple in design and character allowing ease of movement through space. The recommended main water body at the southern edge of the publicly accessible open space acts as an elevated focal point in the Concept Plan site and assists in the creation of a sense of place and provides a connection to the foreshore to the south.

Landscape Design Principles:

- Performs as formal linear open space in addition to its role as a pedestrian link
- Incorporates formal avenue tree planting as a way of screening the adjoining existing building
- Includes clear sight lines through the open space to maximise pedestrian safety
- Includes large reflection pond/water body

9.7. New Upper Riparian Foreshore Link Publicly Accessible Open Space (Development Stages 6 & 7): This new publicly accessible open space will be delivered as part of Indicative Development Stages 6 & 7 This new publicly accessible open space is located between Constitution Rd and Nancarrow Ave in a natural overland flow path and includes part of Council's main stormwater easement for the area.

The intent of this publicly accessible open space is to create a natural landscape with meandering 'riparian' gardens and water features. Natural water features will be designed to account for seasonal fluctuations in water volumes. Swathes of native grass and shrubs will provide interest along the pedestrian pathways which traverse this open space. It is intended that water features abut some of the buildings to accentuate the architecture within a riparian environment. Open lawns and shade trees provide space for residents and visitors to stay and enjoy the peaceful surrounds.

Landscape Design Principles:

- The provision of an easy, safe and enjoyable pedestrian connection with peaceful places to stop and relax
- Optimise ecological functionality through planting of endemic species
- Incorporate overland flow paths into water features within the publicly accessible open space
- Combined active and passive recreation spaces
- Provision of contemplative lawns with shade

13. Tree Management

Tree protection measures will be implemented for trees to be retained as recommended in the Arborist Report at Annexure 23 to the submitted EA.



PEDESTRIAN + CYCLEWAY PLAN (DEVELOPMENT- WIDE)














STREET TREE STRATEGY (DEVELOPMENT-WIDE)



The plan shows the intended tree species to be used in the development. Existing street trees will be assessed on an individual basis to retain if possible. The suitability of the species listed below will also be considered at the detailed design stage and discussed with Council.



Note: All existing street trees will be assessed in light of this plan and retained if appropriate. Ref - Ryde Public Domain Technical Manual - 5.2









LANDSCAPE DESIGN INTENT STATEMENT

journey beginning

The Central Spine is considered the beginning of the escarpment character, the journey begins at the higher end of the two sites along Constitution Road, and continues through a gradual build up in height around the main path, designed in a more softer medium and delivered through landscaped berms and terraces. An elevated walkway branches from the side of the path leading up to a higher level private communal courtyard, whilst incorporating a new story, the tree-top walk

These elements are the beginning of a strong landscape character as well as aiding to respond to the sites level changes. They are also instrumental in the movement of water through the site, ensuring adequate depths and overland flow paths are maintained using a mixture of retaining walls, gradual falls and landscape berming, combined with water sensitive urban design features such as bio-retention basins and dry creek beds (designed to channel water in rain periods).

nexus plazas / heritage responses

Where both stages of the development meet at Nancarrow Road, open plaza spaces have been proposed to ensure fluid movement is encouraged and easy. These central plazas are anticipated to house heritage elements significant to the site, such as an 'orange orchard' within stages 8-9 and the reuse of 1950s style fencing from the old Automatic Totalisors Factory situated on 37 Nancarrow Road on Stage 6-7 side. (See images left)

'factory fencing'

The fencing available for reuse is approximately 47m in 12 sections and is anticipated to either be further explored as part of a public art strategy or to appear as a landscape feature within the podium open space area between building 9A-9B.

'orange orchard'

The Orange Orchard is a reflective and soft landscape with bosque of Orange trees within a decomposed granite surface. Seating has been located under the orange trees and the trees themselves extend beyond the limits of the plaza, drawing the outside in and creating a 'leak' of history into the new development.

escarpment

Moving south from Nancarrow Road plazas, the landscape becomes more severe and levels adjacent the path start to rise higher through gabion and sandstone faced walls. Materials become more 'raw' and reflective of both the landscape journey and the existing / past industrial character, whilst still being modern and architectural in form.

rawness and architectural form

sandstone gabion walls being to move in closer to the path providing elevated rest areas and viewing spaces. Corten panels and steel i-beams integrated with both the gabion walls and into handrails on the upper level, provide a unique design element that adds to the character and style of both the architectural and landscape design.

The path continues to crossroad, where the user can travel west up towards Bowden Street over podium or south towards Rothesay Street.

podium building 9A-9B

the podium landscape is designed in the same nature as the escarpment, with a mixture of raw elements and tidier lines, still with a layering of levels and landscape to provide visual interest and zones for passive recreation.

the podium has also been designed to safely carry overland flow from bowden street through the site and into the bioretention basins.

bbg area (public open space)

Continuing to Rothesay Street, south along the cycle way, a WSUD bioretention basin is incorporated into a flexible public open space area. This area provides an undefined area for casual get-togethers or functions as well as a bbg area and seating.

It is surrounded by terraced planters to compensate dramatic level change, but is still lush with planting, providing ample greenery, shade and amenity. The bio-retention basin is accessible down a set of seating steps and contains a board-walk feature around and over it, making it visually accessible during rain periods and accessible during dry periods.

Residents pool

The pool area is simple in design with clean lines and architectural from + materials, whilst still ensuring a relaxing, casual zone with a high-quality 'sub-tropical' feel to it through the choice of plantings (lush hardy flowering species such as bird of paradise and gymea lily). Planting to be arranged in formal rows of minimal species. The pool is anticipated to reflect the architectural character through reconstituted stone, composite timber decking, ornate pool tiles as examples.

LANDSCAPE DESIGN DRIVERS

Performs as formal linear open space in addition to its role as a pedestrian link

- Incorporates formal avenue tree planting as a way of screening the adjoining existing building
- Includes clear sight lines through the open space to maximise pedestrian safety
- Includes large reflection pond/water body
- The provision of an easy, safe and enjoyable pedestrian connection with peaceful places to stop and relax
- Optimise ecological functionality through planting of endemic species
- Incorporate overland flow paths into water features within the publicly accessible open space
- Combined active and passive recreation spaces
- Provision of contemplative lawns with shade

STAGES 6-7 + 8-9 COMBINED MASTERPLAN





bridge over dry creekbed

connectioning buildings 6-7

service rooms

tree top walk

behind with bio-

retention basin

terraced planter from dry WSUD to

podium courtyard

BUILDING 6

drawings)


(indicative only:

referanchitects

BASEMENT

CARPARK

Development Assessment Submission Stage 6-7 [Meadowbank, Shepherds Bay





Location Plan

CENTRAL SPINE + TREETOP WALK

2.5m wide cycleway . Typical Landscape Bermin to basement wall max 1.0m under adjacent Finished Floor Level BUILDING 7 (indicative only: referanchitects drawings) BASEVIENT CARPARK

bio-retention area 2 (wsud stragtegy) see engineers drawings for detail

private resident access: nancarrow road

connection to building 7 foyer

المراد

PS DIA

DETAILED LANDSCAPE PLAN: CENTRAL SPINE SCALE 1:350 @ A3

REEL

private resident access: constitution road

- 2.5m wide cycleway

dry creek bed (wsud stragtegy) see engineers drawings for detail

native landscape bermed to

fire-stair access + connection

landscape terraced to private

free-top' walk: connection to

basement wall

common area

building 7

landscape bermed to

private common area

gated +fenced private

bio-retention area 1

dry creek bed (wsud)

maintenance / services

maintenance / services access to building 6

bio-retention area 1 (wsud

stragtegy) see engineers

maintenance / services access to building 7

drawings for detail

access to building 7

common area

integration of heritage fences to plaza spaces

SECTION A SCALE 1:100@A3

CENTRAL SPINE / TREE TOP WALK





Location Plan




INDICATIVE PERSPECTIVE OF TREE TOP WALK Artist impression only







BUILDING 6 - PRIVATE COMMON AREA



drawings)





Timber shade structure overbbq / sitting area with climbers

SCALE 1:200 @ A3

Location Plan

INDICATIVE CHARACTER IMAGES






SCALE 1:350 @ A3

DETAILED LAND SCAPE PLAN: PODIUM COURTYARD / PRIVATE COMMON


SECONDARY SITE LINKS: WEST + EAST







DETAILED LANDSCAPE PLAN: EAST LINK SCALE 1:350@ A3



'Rest Zone' with seating to edge of access path Landscape treatment to building, mainting access to service panels and creating visual aesthetic and casual access path to private survillance to path residencies Columnar tree with planting under to boundary for softening and screening 1.8m high timber paling fence to boundary BUILDING7 (indicative only: refer architects drawings) FFL9.600 - Maintenance access maintained to service RL7.390 RL 7.400 panels and vents FFL6.585 SECTION E

SCALE 1:50@ A3

NANCARROW ROAD FRONTAGE


Streetscape Design Philopsphy

Street trees throughout the site will be reflective of the Meadowbank street tree master plain. The street tree design to the site is intended to enhance strong legible links, providing biodiversity and aesthetic consistency across the site, both in streets capes and site through links.

The planting will reference the DCP, Council Public Domain Technical Manual and Council guidelines.

Refer to WSUD document for detail on rain gardens. The design of rain-gardens will be to Ryde city council specifications and in line with Ryde city council maintenance plan.








Loading Bay -

Row of Angophora floribunda -







STAGE 6-7 TREE / SOFTSCAPE STRATEGY

GENERAL TREE MIX (Native + Exotic) (Public Open Space + Residential)

Cupaniopsis ana cardiodes - Tuckeroo Elaeocarpus reticulatus - Blueberry Ash Ficus macrophylla - Moreton Bay Fig Fraxinus griffithii - Evergreen Ash Fraxinus oxycarpa - Raywood Claret Ash Lagerstroemia indica - Crepe Myrtle Lagerstroemia speciosa - Giant Grepe Myrtle La gerstroemia indica fauriei - Grepe Myrtle Acoma Lophostemon confertus - Brush Box Pistas da chinensis - Chinese Pistache Plantus x Hybrida - Chinese Tallyvood Pyrus calleryana 'Chantideer' - Manchurian Pear apiumserbiferum - Chinese Tallowood Ulmus parvifolia - Chinese Elm Waterhousia floribunda - Weeping Lily Pily



PALMS (Public Open Space + Residential)

Archontophoenix Cunninghamiana - Bangalow Palm Archontophoenix alexandrae - Alexandra Palm Livisto na australis - Cabbage Tree Palm Phoenix canariensis - Canary Palm

NATIVE TREES (Public Open Space + WSUD)

Angophora costata - Sydney Red Gum Angophora floribunda - Rough-Barked apple Cupaniopsis anacardio des - Tuckeroo Corymbia Maculata - Spotted Gum Elaeocarpus reticulatus - Blueberry Ash Ficus macrophylla - Moreton Bay Fig. Lophostemon confertus - Brush Box Melaleuca species - Paperbarks Syncarpia glomulifera - Turpentine Tristaniopsis laurina - Water Gum Waterhousia floribunda - Weeping Lily Pily



FEATURE TREES (Public Open Space) Ficus macrophylla - Moreton Bay Fig Magnolia grandiflora Little Gem´ - Magnolia

(Locations as indicated on plans)

Angophora costata - Sydney Red Gum

Fraxinus oxycarpa - 'Raywood' Claret Ash

Angophora floribunda - Rough-Barked apple

Magnolia grandiflora - Little Gemi

Syncarpia glomulifera - Turpentine

HERITAGE TREES

Citrus x sinensis - Orange Tree

Fraxinus griffithii - Evergreen Ash



TURF



GENERAL PLANTING MIX Exotic + Native (see indicate planting schedule)



WSUD PLANTING MIX Native Species Only (see indicative planting schedule)



RETAINED TREES

See aborist report



The Planting palette to be used throughout the site has been selected for it's suitability to fulfill the following criteria:

- Enhance the local character of Meadowbank
- Create a new defined precinct
- Remain in line with the City of Ryde's environmental policies
- Soften and visually reduce bulk/scale of built forms
- Provide buffering/screening to residential areas
- Contribute to habitats of the local fauna
- Minimise potable water use in the landscape

A wide selection of trees, both native and exotic, have been selected for the sites streets capes and landscaped areas. Where possible local natives will be used to remain consistent with the vegetation communities found within the City of Ryde. Specific areas will see exotic species used for accent planting and foliage interest

Shrubs have been chosen not only for their aesthetic attributes but also functionality in terms of providing buffering and screening to residential precincts. Lush foliage and dense growing habits have been favoured.

Grasses and groundcovers have been selected from a predominantly native palette and will be aimed at softening edges and large areas of hardscape













STAGE 6-7 INDICATIVE PLANTING SCHEDULE

Streetscape Trees

Botanical Name	Common Name	Height + Spread (h x w)	Container Size	plants per m2
Angophora costata	Sydney Red Gum	20.0m x 8.0m	75L	As Shown
Magnolia grandiflora	'Little Gem'	4.0m x 3.0m	75L	As Shown
Fraxinus griffithii	Evergreen Ash	6.0m x 4.0m	75L	As Shown
Fraxinus oxycarpa	'Raywood' Claret Ash	12.0m x 12.0m	75L	As Shown
Syncarpia glomulifera	Turpentine	20.0m x 8.0m	75L	As Shown
Angophora floribunda	Rough-Barked apple	20.0m x 8.0m	75L	As Shown

General Planting

Botanical Name	Common Name	Height + Spread (h x w)	Container Size	plants per m2
TREES				
evergreen				
Angophora costata	Smooth Barked Apple	20.0m x 8.0m	75L	As Shown
Corymbia maculata	Spotted Gum	30.0m x 15.0m	75L	As Shown
Cupaniopsis anacardioides	Tuckeroo	8.0m x 8.0m	75L	As Shown
Elaeocarpus reticulatus	Blueberry Ash	10.0 x 7.0m	75L	As Shown
Ficus macrophylla	Moreton Bay Fig	.30.0m x 20.0m	75L	As Shown
Fraxinus omus	Meczek	20.0m x 10.0m	75L	As Shown
Lophostemon confertus	Brush Box	10.0m x 12.0m	75L	As Shown
Tristaniopsis laurina 'Luscuious'	Water Gum	12.0m x 8.0m	75L	As Shown
Waterhousia floribunda	Weeping Lily Pily	12.0m x 8.0m	75L	As Shown
PALMS		·		
Archontophoenix cunninghamiana	Bangalow Palm	25.0m × 3.0m	200L	As Shown
Archontophoenix alexandrae	Alexandra Palm	30.0m x 2.0m	200L	As Shown
Livistona australis	Cabbage Tree Palm	25.0m x 3.0m	400L	As Shown
Phoenix canariensis	Canary Palm	18.0m x 8.0m	400L	As Shown
DECIDUOUS	To account On a Title	1.51-1111111111111111111111111111111111		7.5.5115.1111
Acer platanoides	Designer Maple 'Globosum'		200L	As Shown
Acer palmatra	Osakazuki		200L	As Shown
Lagerstroemia indica' Lipan'	Crepe Myrtle	4.0m x 3.0m	200L	As Shown
Lagerstroemia speciosa	Giant Crepe Myrtle	3.0m x 3.0m	200L	As Shown
Lagerstroemia indica fauriei	Acoma	8.0m x 6.0m	400L	As Shown
Pistascia chinensis	Chinese Pistache	10.0m x 4.0m	75L	As Shown
Plantus x Hybrida	Plane Tree	20.0m x 9.0m	75L	As Shown
Pyrus calleryana 'Chanticleer'	Manchurian Pear	11.0m x 6.0m	75L	As Shown
Sapium sebiferum	Chinese Tallowood	8.0m x 4.0m	75L	As Shown
12			75L	
Ulmus parvifolia	Chinese Elm	14.0m x 10.0m	/ 5L	As Shown
FEATURE TREES	I 6	0.0/.0	4001	A - Ch
Citrus x sinensis	Orange	9.0m x 6.0m	400L	As Shown
Ficus macrophylla	Moreton Bay Fig	35.0 x 25.0m	400L	As Shown
Magnolia grandiflora 'Little Gem'	Magnolia	4.0m x 3.0m	400L	As Shown
SHRUBS + ACCENT				
Acacia parramattensis	Sydney Green Wattle	4.0m x 3.0m	25L	As Shown
Acacia falcata	Sickle-shaped Acacia	4.0m x 1.5m	25L	As Shown
Banksia serrata	Dwarf Bottlebrush	2.0m x 2.0m	5L	4/m2
Cordyline australis	Sunrise	3.0m x 1.0m	25L	As Shown
Cordyline sp	Cordyline	3.0m x 1.0m	25L	As Shown
Dodonaea triquetra	Hop Bush	3.0m x 2.0m	300mm	4/m2
Dodonaea viscosa 'Purpurea'	Hop Bush	3.0m x 1.5m	300mm	4/m2
Doryanthes excelsa	Gymea Lily	1.5m x 1.5m	25L	1/m2
Gardenia augusta 'Florida'	Gardenia	1.2m 1.0m	.25L	4/m2
Kunzea ambiqua	Tick Bush	5.0m x 5.0m	300mm	As Shown
Murraya paniculata	Orange Jessamine	3.0m × 3.0m	25L	As Shown
Philodendron 'Xanadu'	Xanadu	1.5m x 1.5m	200mm	5/m2
Strelitzia reginae	Bird of Paradise	1.5m x 1.0m	300mm	3/m2
Syzygium sp.	Lilly Pilly	Varies	25L	2/m2
oyzygium sp. Viburnum odoratissimum	Sweet vibumum	4.0m x 4.0m	25L 25L	2/11/2 1/m2
Westringia fruticosa 'Zena'	Costal Rosemary	1.0m x 1.3m	300mm	4/m2

Botanical Name	Common Name	Height + Spread (h x w)	Container Size	plants per m2
GROUNDCOVERS /	GRASSES			
Altenanthera dentata	Blood Leaf Irisene	40mm x 90mm	200mm	5/m2
Dichondra repens	Kidney Weed	150mm x 500mm	200mm	3/m2
Dianella 'Breeze'	Paroo Lily	300mm x 300mm	200mm	4/m2
Dianella 'Little Jess'	Paroo Lily	400mm x 600mm	140mm	4/m2
Dianella 'Silver Streak'	Paroo Lily	500mm x 400mm	1 40mm	4/m2
Gazania hybrida	Gazania Double Gold	300mm x 300mm	200mm	5/m2
Hardenbergia 'Purple Spray'	Native Violet	1.5m x 2.0m	200mm	2/m2
Hibbertia scandens	Snake Vine	3.0m x 3.0m	200mm	2/m2
Isolepis nodosa	Club Rush	500mm x 300mm	1 40mm	4/m2
Juncus usitatus	Common Rush	500mm x 300mm	1 40mm	4/m2
Liriope 'El Marco'	Turf Lily	150mm x 400mm	140mm	4/m2
Lomandra hystrix	Mat Rush	0.6m x 1.0m	140mm	4/m2
Lomandra longifolia 'Tanika'	Mat Rush	600mm x 650mm	200mm	4/m2
Poa labillardieri 'Eskdale'	Tussock Grass	800mm x 400mm	200mm	4/m2
Scaevola aemula	Fairy Fan-flower	0.2m x 1.5m	200mm	4/m2
Trachelospermum jasminoides	Star Jasmine	0.4m x 1.5m	200mm	4/m2

WSUD (Dry Creek Bed + Bio-retention)

Botanical Name	Common Name	Height + Spread (h x w)	Container Size	plants per m2
TREES / PALMS	-			
Ficus macrophylla	Moreton Bay Fig	30.0m x 20.0m	75L	As Shown
Corymbia maculata	Spotted Gum	30.0m x 15.0m	75L	As Shown
Lophostemon confertus	Brush Box	10.0m x 12.0m	75L	As Shown
Tristaniopsis laurina 'Luscuious'	Water Gum	12.0m x 8.0m	75L	As Shown
Livistona australis	Cabbage Tree Palm	25.0m x 3.0m	400L	As Shown
Waterhousia floribunda	Weeping Lily Pily	12.0m x 8.0m	75L	As Shown
GROUNDCOVERS /	GRASSES			
Dianella 'Breeze'	Paroo Lily	300mm x 300mm	200mm	4/m2
Dianella 'Little Jess'	Paroo Lily	400mm x 600mm	140mm	4/m2
Dianella 'Silver Streak'	Paroo Lily	500mm x 400mm	140mm	4/m2
Isolepis nodosa	Club Rush	500mm x 300mm	140mm	4/m2
Juncus usitatus	Common Rush	500mm x 300mm	140mm	4/m2
Liriope 'El Marco'	Turf Lily	150mm x 400mm	1 40mm	4/m2
Lomandra hystrix	Mat Rush	0.6m x 1.0m	1 40mm	4/m2
Lomandra longifolia 'Tanika'	Mat Rush	600mm x 650mm	200mm	4/m2

Note: The term 'as shown' denotes need to place individual plant species for desired landscape outcomes

STAGE 6-7 STREETSCAPE STRATEGY

NOTE: STREETSCAPES WILL BE DESIGNED EXACTLY IN ACCORDANCE WITH THE RYDE CITY COUNCIL PUBLIC DOMAIN MANUAL

Design Intent

The Shepherds Bay Streets cape Character and Tree Species will reflect the character of the site whilst accommodating for the requirements of Council. The functional needs of pedestrians, cyclists and vehicular movements will also be paramount in the design of vehicular carriage ways.

The streetscape character will generally reinforce and enhance the road hierarchy to create subtle but distinctive streetscape precincts. The formal planting of mid to large size trees on Primary Local Roads (Dependant on Council approval) and the introduction of smaller native species on Secondary Local Roads will occur. A combination of both native and hybrid indigenous trees must dominate the selection of street trees to the internal roads.

Streets are to be designed to provide an appropriate level of on street parking with priority given to pedestrians and cyclists to provide a pleasant environment to promote walking and social activity.

Some key points are listed below;

Aspect and Views

- Strong visual associations with existing vegetation communities both native and cultural.
- Use of Landmark species to clearly identify entry points into the development.
- Strong emphasis to avenue planting with spacings of trees to enable canopies to touch when trees are mature.

Accessibility

- Continuity of streets cape character and connectivity to local and recreational paths linking the entire site.

Materials

- Pathways will predominantly be robust contemporary materials such as exposed aggregate concrete. All driveway cross overs are to be of the same material in order to ensure visual continuity.

Plantings:

- Maximise landscaping in all streets while tailoring species selection to that of the local and site context.
- Preservation of plantings of culturally significant species to enhance the historic 'sense of place'
- Canopy trees to provide shade and visual amenity.
- Low shrub and groundcover planting using a mix of low maintenance plant species

Safety:

- All street trees will be carefully selected so that the pedestrian sight lines are well maintained.
- Street lighting and feature lighting will also be carefully designed to meet the safety criteria for

pedestrian/cycle and car links.

Indicative Materials + Elements

CONSTITUTION ROAD

Carriageway Thresholds 100 x 100 x 60mm Australian Porphyry Stone

Tree Pits

Minimum 1500mm x 1500mm resin bound gravel (grey colour)

Banding

300 x 300 x 60mm Grey Granite Banding

Paving

600 x 300 x 60mm Grey Granite Paving and 300 x 300 x 60mm Grey Granite Paving

Lighitng

Smart Poles at 9.6m spacings (between trees)

Trees

8m Spacings

Tree Species

Verge (6-7 Frontage) Angophora costata)

NANCARROW ROAD

Carriagevvay Thresholds

100 x 100 x 60mm Australian Porphyry Stone

Tree Pits

1500mm x 1500mm resin bound gravel (grey colour)

Bandino

300 x 300 x 60mm Grey Granite Banding

Paving

600 x 300 x 60mm Grey Granite Paving and 300 x 300 x 60mm Grey Granite Paving

Lighitng

Smart Poles at 9.6m spacings (between trees)

Rain Gardens

To council specifications

Trees

8m Spacings

Tree Species

Northern Verge (6-7 Frontage) Angophora floribunda (Rough-barked Apple) Southern Verge (8-9 Frontage) Magnolia grandiflora ('Little Gem')

Indicative Tree Palette + Planting Character



Constitution Road Northern Verge (6-7 Frontage) Angophora costata




Indicative character where additional planting is proposed

Stag

8 - 9

KEY



NOTE: REFER ABORIST REPORT FOR SPECIES AND DETAILED TREE INFORMATION

STAGES 8+9

(See Landscape Package 8+9)

STAGE 6-7 LANDSCAPE MATERIALITY

Indicative Materials Palette: Streetscape Selected images from Ryde Public Domain Technical Manual + Place Design Group




















STAGE 6-7 MATERIALS STRATEGY




Indicative Pavement Schedule

- P1 Standard concrete to shared 2.5m wide cycleway (as per Ryde Public Diomain Plan) + general pedestrian paths
- P2 Precast high quality concrete/limestone pavers with sandstone porphry banding and header
- P3 Decomposed Granite (not used in this stage)
- P4 Mixed colour sandstoine paving to private courtyards 600x300x60mm
- P5 Limestone (High Quality) Pool Area (not used in this stage)
- P6 Reconsituted timber deck
- P7 Streets cape: Grey granite / limestone pavers 600x300x60 + 300x300x60mm (Ryde PD TM)
- P8 Streetscape: Australian perphery stone on threshold 100x100x60mm (Ryde PDTM)
- P9 Resin bound gravel to base of trees (as per Ryde Public Domain Plan)

Indicative Walling Schedule

- W1 Sandstone dad walls (height varies) generally used for retaining walls + planters
- W2 Instu/ Precast white concrete wall (generally used as seating steps to turf planters)
- W3 Sandstone Gabion Walls (not used in this stage)



Type 1: Main Paver Stone Type: Limestone Colour: Light Grey Finish: Natural Size: 600x300x30mm

Type 2: Banding Stone Porphory Cobbles Colour: Grey Finish: 5 plit SheetSize: 300x300x12mm

Example of P2 pavement treatment: Precast high quality concrete/limestone pavers with sandstone porphry banding and header coursecourtyards







Type 2: Bainding Stone Type: River Travertine 5'æe: 600x400x30mm Finish: Sandblasted

Type 3: Feature Banding Stone Type: Porphory Setts Finish: Sandblasted

Example of P4 pavement treatment: Mixed colour sandstone paving to private courtyards

STAGE 6-7 LIGHTING STRATEGY





Pedestrian & Vehicular Lighting Street lighting

Mounted on 9.6m multifunction poles to Council approval. Finish on poles to match existing poles in Belmore Street. Poles to be provided with 1.5m banner arm, Rexel Optispan Aeroscreen luminaires complete with low loss ballasts and PE cells, and metal halide lamps.



Pedestrian/park lighting

For areas such as shared bikeway/pedestrian pathways and plazas. Mounted on 4.8 m

Smartpoles TM or approved equivalent. BEGA-8081 luminaires and metal halide lamps.



Solar lighting for parks (* Courtyards)

Supplier: Solar G

Pole: galvanised utility pole

Light fittings: "Streetwalker" on 1metre outreach arm Lamps: 2x 14W fluorescent (T5 fluorescent technology, 96

umens per watt

Note: Due to the lack of sunlight in some areas we will

propose a different fitting/light pole



Feature columnar Lighting

Supplier: Bega

Lightstructure: 2.5 high aluminium linear element with white

acrylic diffuser. IP65 Lamps: 151.2W LED

NOTE: Diagram is a strategy only, and is dependant on future detail design for specific information on products and locations

STAGE 6-7 FURNITURE STRATEGY

- Bins (Bin 1)
 Council's standard double bin.
- Bollards (Bollard 4)
 1300mm high x 150mm dia
 1.6mm thick 316 stainless steel
 Core drilled to depth of 400mm
 Colorfen Constructions
 Ph (02) 9545 4284
- Bespoke seating elements (concrete benches)
- Urban Seat 11 (aluminium)

 Botton and Gardiner Urban furniture ph (02) 9667 8100
- Bicycle Racks
 Environ Bike Racks ENV09
 Urban Art Projects
- Heritage Fencing (Resued from site)

Ref. City of Ryde Public Domain R+Technical Manual - 5.2

NOTE: Diagram is a strategy only, and is dependent on future detail design for specific information on products and locations





26

STAGE 6-7 ROOFTOP GARDEN STRATEGY







BENEFITS OF RELOCATABLE ROOFTOP PLANTERS

- containers are movable
- no set down
- suitable weight bearing structure not needed







APPENDIX A performance specifications