



NOTES:

1. THIS SUBSTRATA RESTORATION DETAIL APPLIES TO ALL KERB AND GUTTER AND DRIVEWAY LAYBACK.
2. REFER TO DRAWING PL7.1 FOR TURFING DETAIL INCLUDING TOP SOIL CULTIVATION
3. PROVIDE 50mm SAWCUT AND REINSTATE 300 TO 500mm INTO ROAD PAVEMENT FROM GUTTER LIP UNLESS OTHERWISE INSTRUCTED BY COUNCIL ENGINEER.
4. IF SUBBASE AND SUBGRADE IS IN POOR CONDITION, REINSTATE OF PAVEMENT TO BE DISCUSSED WITH COUNCIL ENGINEER AFTER REMOVAL OF EXISTING KERB & GUTTER.
5. ALL DIMENSIONS IN MILLIMETRES UNLESS NOTED OTHERWISE.

COPYRIGHT © 2011 City of Ryde - ALL RIGHTS RESERVED
No part of this document shall be modified or reproduced without written permission.
Go to www.ryde.nsw.gov.au/disclaimer to view the Standard Drawings Disclaimer



ABN: 81 621 292 610
LEVEL 1, BUILDING 0, BINARY CENTRE, 3 RICHARDSON PLACE, NORTH RYDE NSW 2113
Locked Bag 2069
NORTH RYDE NSW 1670
Email: cityofryde@ryde.nsw.gov.au
Web: www.ryde.nsw.gov.au
Tel: (02) 9952 8222
Fax: (02) 9952 9070

STANDARD DRAWING
**KERB AND GUTTER
REPLACEMENT AND RESTORATION WORKS**

APPROVED VP DESIGN MANAGER	DATE 21/06/18
DRAWING NUMBER	REVISION
CIV.1.2.1	F