



NOTES:

- TOOLED JOINTS AND EXPANSION JOINTS SHALL BE PROVIDED AT THE SAME SPACING AS THE CONCRETE FOOTPATH. REFER TO CIV.5 SERIES FOR JOINTS SPACING AND CIV.11 FOR JOINT DETAILS.
- REMOVE AIR BUBBLES AND PREVENT HONEY COMBING BY AERATING OR VIBRATING CONCRETE FORMWORK.
- ALL CONCRETE CORNER SHALL BE CHAMFERED BY 25mm UNLESS NOTED OTHERWISE.
- MINIMUM CONCRETE COVER SHALL BE 50mm UNLESS NOTED OTHERWISE.
- CONCRETE EDGES SHALL BE FINISHED WITH AN EDGING TOOL.
- CONCRETE SHALL HAVE A 28 DAY STRENGTH OF 25MPa MINIMUM.
- CONCRETE SHALL BE PLACED WITH A MAXIMUM SLUMP OF 80mm.
- ALL DIMENSIONS IN MILLIMETRES UNLESS NOTED OTHERWISE.

COPYRIGHT © 2011 City of Ryde - ALL RIGHTS RESERVED
No part of this document shall be modified or reproduced without written permission.
Go to www.ryde.nsw.gov.au/disclaimer to view the Standard Drawings Disclaimer



ABN: 81 621 292 610
LEVEL 1, BUILDING 0, BINARY CENTRE, 3
RICHARDSON PLACE, NORTH RYDE NSW 2113
Locked Bag 2069
NORTH RYDE NSW 1670
Email: cityofryde@ryde.nsw.gov.au
Web: www.ryde.nsw.gov.au
Tel: (02) 9952 8222
Fax: (02) 9952 8070

STANDARD DRAWING
FOOTPATH HOB WALL

APPROVED VP DESIGN MANAGER	DATE 24/06/16
DRAWING NUMBER	REVISION
CIV.10	C